

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL




KEMP QUARRIES / BCS - MILL CREEK [66781] TTT008 Component

Transmission (Manual)

Fluid PETRO CANADA PROI		(GAL)	De	c2019	Feb2023 Mar20	24	
DIAGNOSIS	SAMPLE INFO	RMATION	method	limit/base	current	history1	history2
ecommendation	Sample Number		Client Info		PCA0108979	PCA0086700	PCA46228005
lesample at the next service interval to monitor. (Sample Date		Client Info		11 Mar 2024	02 Feb 2023	05 Dec 2019
ustomer Sample Comment: PM-1 sampled fluid)	Machine Age	hrs	Client Info		7033	6859	6341
ear	Oil Age	hrs	Client Info		7033	6859	0
l component wear rates are normal.	Oil Changed		Client Info		N/A	Changed	N/A
ontamination	Sample Status				NORMAL	NORMAL	NORMAL
nere is no indication of any contamination in the id.	CONTAMINA	TION	method	limit/base	current	history1	history2
uid Condition	Water		WC Method	>0.1	NEG	NEG	NEG
The condition of the fluid is acceptable for the time n service.	WEAR META	LS	method	limit/base	current	history1	history2
	Iron	ppm	ASTM D5185m	>200	20	39	23
	Chromium	ppm	ASTM D5185m	>5	<1	<1	0
	Nickel	ppm	ASTM D5185m	>5	0	0	0
	Titanium	ppm	ASTM D5185m		<1	<1	0
	Silver	ppm	ASTM D5185m	>7	0	0	0
	Aluminum	ppm	ASTM D5185m	>25	2	4	3
	Lead	ppm	ASTM D5185m	>45	<1	<1	0
	Copper	ppm	ASTM D5185m	>225	8	42	2
	Tin	ppm	ASTM D5185m	>10	<1	<1	0
	Vanadium	ppm	ASTM D5185m		0	0	0
	Cadmium	ppm	ASTM D5185m		0	0	0
	ADDITIVES		method	limit/base	current	history1	history2
	Boron	ppm	ASTM D5185m	2	3	6	22
	Barium	ppm	ASTM D5185m	0	0	0	0
	Molybdenum	ppm	ASTM D5185m	0	3	2	0
	Manganese	ppm	ASTM D5185m	9	<1	<1	0
	Magnesium	ppm	ASTM D5185m	1	30	31	19
	Calcium	ppm	ASTM D5185m	3131	2628	3022	2600
	Phosphorus	ppm	ASTM D5185m	1194	932	1052	995
	Zinc	ppm	ASTM D5185m	1281	1121	1239	1011
	Sulfur	ppm	ASTM D5185m	3811	4480	8119	
	CONTAMINA	NTS	method	limit/base	current	history1	history2
	Silicon	ppm	ASTM D5185m	>125	15	13	9
	Sodium	ppm	ASTM D5185m		0	0	2
	Potassium	ppm	ASTM D5185m	>20	2	2	2
	VISUAL		method	limit/base	current	history1	history2
	White Metal	scalar	*Visual	NONE	NONE	NONE	
	Yellow Metal	scalar	*Visual	NONE	NONE	NONE	
	Precipitate	scalar	*Visual	NONE	NONE	NONE	
	Silt	scalar	*Visual	NONE	NONE	NONE	
	Debris	scalar	*Visual	NONE	NONE	NONE	
	Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	
	Appearance	scalar	*Visual	NORML	NORML	NORML	
	Odor	scalar	*Visual	NORML	NORML	NORML	
	Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	
	Free Water	scalar	*Visual		NEG	NEG	



OIL ANALYSIS REPORT



					limit/base	current	history1	history2
		/isc @ 40°C	cSt	ASTM D445	88.5	87.5	95.1	
		SAMPLE IMA	GES	method	limit/base	current	history1	history2
	C	Color				no image	no image	no image
	U	000				no image	nonnage	no image
Mar11/24								
	В	ottom				no image	no image	no image
		GRAPHS Iron (ppm)				Lead (ppm)		
	400	Severe			10			
	300-				8			
	튭 200	Abnormal			E 4	Abnormal		
	100				2			
	0							
		Dec5/19	Feb2/23		Mar11/24	Dec5/19 -	Feb2/23	
		Aluminum (ppm))		2	Chromium (p	opm)	
	50	Severe			12	Severe		
	40 - 30 -							
	ud 20 -	Abnormal			bb	Abnormal		
	10-					2	1	
	0	6.	23-				23	č
		Dec5/19	Feb2/23		Mar11/24	Dec5/19	Feb2/23	
	500 -	Copper (ppm)			30	Silicon (ppm))	
	400	Severe			25	Courses.		
	300 -	Abnomal			20 톮 15	1		
	² 200-	Abnormal			10			
	100-				5)		
	0-	Dec5/19	Feb2/23 -		Mar11/24	Dec5/19	Feb2/23 -	5
		ے Viscosity @ 40°C			Mai	≞ Additives	Ľ	2
	100				350	°T		
			/		300	essesses phosphor	us	
	95-							
		Base			<u>a</u> 200]		
	_	Abnormal			150)+		
	(10,000 (10,000) (10,		Feb2/23 -)	Feb.2/23	