




OIL ANALYSIS REPORT

Sample Rating Trend

FUEL



Area
(P500890)
Machine Id
2363
Component
Diesel Engine
Fluid
PETRO CANADA DURON SHP 15W40 (60 QTS)



DIAGNOSIS

Recommendation

The oil change at the time of sampling has been noted. We recommend an early resample to monitor this condition.

Wear

All component wear rates are normal.

Contamination

There is a moderate amount of fuel present in the oil. Tests confirm the presence of fuel in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The oil is no longer serviceable due to the presence of contaminants.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		GFL0101788	GFL0081015	GFL0070792
Sample Date	Client Info		18 Mar 2024	04 Aug 2023	03 Mar 2023
Machine Age	mls	Client Info	415500	414900	414900
Oil Age	mls	Client Info	600	600	600
Oil Changed	Client Info		Changed	Changed	Changed
Sample Status			ABNORMAL	ABNORMAL	MARGINAL

CONTAMINATION

	method	limit/base	current	history1	history2
Water	WC Method	>0.2	NEG	NEG	NEG
Glycol	WC Method		NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >120	71	19	47
Chromium	ppm	ASTM D5185m >20	4	<1	1
Nickel	ppm	ASTM D5185m >5	1	<1	<1
Titanium	ppm	ASTM D5185m >2	<1	0	<1
Silver	ppm	ASTM D5185m >2	0	0	0
Aluminum	ppm	ASTM D5185m >20	5	3	6
Lead	ppm	ASTM D5185m >40	7	<1	17
Copper	ppm	ASTM D5185m >330	4	<1	3
Tin	ppm	ASTM D5185m >15	1	<1	<1
Vanadium	ppm	ASTM D5185m	0	0	<1
Cadmium	ppm	ASTM D5185m	0	0	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	6	28	56
Barium	ppm	ASTM D5185m 0	0	0	0
Molybdenum	ppm	ASTM D5185m 60	83	60	80
Manganese	ppm	ASTM D5185m 0	<1	<1	<1
Magnesium	ppm	ASTM D5185m 1010	1222	579	709
Calcium	ppm	ASTM D5185m 1070	1429	1248	1245
Phosphorus	ppm	ASTM D5185m 1150	1281	866	812
Zinc	ppm	ASTM D5185m 1270	1640	1071	1004
Sulfur	ppm	ASTM D5185m 2060	4190	3014	2419

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	12	4	11
Sodium	ppm	ASTM D5185m	5	<1	9
Potassium	ppm	ASTM D5185m >20	6	2	10
Fuel	%	ASTM D3524 >3.0	▲ 3.0	▲ 4.6	▲ 4.7

INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >4	3.1	2	3.9
Nitration	Abs/cm	*ASTM D7624 >20	9.0	7.2	11.1
Sulfation	Abs/.1mm	*ASTM D7415 >30	23.9	20.1	27.4


FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	14.9	12.0	17.0
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	7.1	7.8	6.3




OIL ANALYSIS REPORT


▲ Fuel Dilution



Base Number



Viscosity @ 100°C




VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG


FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	14.1 ▲	12.4

GRAPHS


Ferrous Alloys




Non-ferrous Metals



Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513

Sample No. : GFL0101788

Lab Number : 06121941

Unique Number : 10936092

Test Package : FLEET (Additional Tests: PercentFuel)

Received : 19 Mar 2024

Tested : 21 Mar 2024

Diagnosed : 21 Mar 2024 - Wes Davis

GFL Environmental - 030 - Conway Myrtle Beach

3010 HWY 378

Conway, SC

US 29527

Contact: ARCILIO RUEZ

arui@gflenv.com

T:

F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)