




OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Machine Id
99M
Component
Diesel Engine
Fluid
PETRO CANADA DURON SHP 15W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

Insufficient sample was received to conduct all the routine laboratory tests. There is no indication of any contamination in the oil.

Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORMATION

| | method | limit/base | current | history1 | history2 |
|---------------|-------------|-------------|--------------------|-------------|-------------|
| Sample Number | Client Info | | GFL0104435 | GFL0110149 | GFL0110051 |
| Sample Date | Client Info | | 12 Mar 2024 | 13 Feb 2024 | 23 Jan 2024 |
| Machine Age | mls | Client Info | 284614 | 20274 | 20142 |
| Oil Age | mls | Client Info | 0 | 600 | 600 |
| Oil Changed | Client Info | | Not Chngd | Changed | Changed |
| Sample Status | | | NORMAL | NORMAL | NORMAL |

CONTAMINATION

| | method | limit/base | current | history1 | history2 |
|--------|-----------|------------|----------------|----------|----------|
| Fuel | WC Method | >5 | <1.0 | <1.0 | <1.0 |
| Water | WC Method | >0.2 | NEG | NEG | NEG |
| Glycol | WC Method | | NEG | NEG | NEG |

WEAR METALS

| | method | limit/base | current | history1 | history2 |
|----------|--------|------------------|--------------|----------|----------|
| Iron | ppm | ASTM D5185m >80 | 17 | 23 | 3 |
| Chromium | ppm | ASTM D5185m >5 | <1 | <1 | 0 |
| Nickel | ppm | ASTM D5185m >2 | <1 | 0 | <1 |
| Titanium | ppm | ASTM D5185m | <1 | <1 | 0 |
| Silver | ppm | ASTM D5185m >3 | 0 | 0 | 0 |
| Aluminum | ppm | ASTM D5185m >30 | 3 | 6 | 2 |
| Lead | ppm | ASTM D5185m >30 | <1 | 0 | 0 |
| Copper | ppm | ASTM D5185m >150 | <1 | <1 | 0 |
| Tin | ppm | ASTM D5185m >5 | <1 | <1 | <1 |
| Vanadium | ppm | ASTM D5185m | 0 | 0 | 0 |
| Cadmium | ppm | ASTM D5185m | 0 | 0 | 0 |

ADDITIVES

| | method | limit/base | current | history1 | history2 |
|------------|--------|------------------|--------------|----------|----------|
| Boron | ppm | ASTM D5185m 0 | 2 | <1 | 2 |
| Barium | ppm | ASTM D5185m 0 | 0 | 0 | <1 |
| Molybdenum | ppm | ASTM D5185m 60 | 57 | 56 | 53 |
| Manganese | ppm | ASTM D5185m 0 | <1 | 0 | <1 |
| Magnesium | ppm | ASTM D5185m 1010 | 916 | 926 | 839 |
| Calcium | ppm | ASTM D5185m 1070 | 1042 | 1000 | 909 |
| Phosphorus | ppm | ASTM D5185m 1150 | 1014 | 1028 | 947 |
| Zinc | ppm | ASTM D5185m 1270 | 1233 | 1238 | 1115 |
| Sulfur | ppm | ASTM D5185m 2060 | 3237 | 3081 | 2728 |

CONTAMINANTS

| | method | limit/base | current | history1 | history2 |
|-----------|--------|-----------------|----------|----------|----------|
| Silicon | ppm | ASTM D5185m >20 | 5 | 5 | 5 |
| Sodium | ppm | ASTM D5185m | 3 | 4 | 2 |
| Potassium | ppm | ASTM D5185m >20 | 4 | <1 | 2 |

INFRA-RED



| | method | limit/base | current | history1 | history2 |
|-----------|----------|-----------------|------------|----------|----------|
| Soot % | % | *ASTM D7844 >3 | --- | 0.2 | 0.1 |
| Nitration | Abs/cm | *ASTM D7624 >20 | --- | 6.7 | 4.8 |
| Sulfation | Abs/.1mm | *ASTM D7415 >30 | --- | 18.3 | 17.6 |

FLUID DEGRADATION

| | method | limit/base | current | history1 | history2 |
|------------------|----------|-----------------|------------|----------|----------|
| Oxidation | Abs/.1mm | *ASTM D7414 >25 | --- | 14.6 | 13.1 |
| Base Number (BN) | mg KOH/g | ASTM D2896 9.8 | --- | 8.6 | 9.1 |







OIL ANALYSIS REPORT



| VISUAL | method | limit/base | current | history1 | history2 |
|------------------|--------|------------|---------|----------|----------|
| White Metal | scalar | *Visual | NONE | NONE | NONE |
| Yellow Metal | scalar | *Visual | NONE | NONE | NONE |
| Precipitate | scalar | *Visual | NONE | NONE | NONE |
| Silt | scalar | *Visual | NONE | NONE | NONE |
| Debris | scalar | *Visual | NONE | NONE | NONE |
| Sand/Dirt | scalar | *Visual | NONE | NONE | NONE |
| Appearance | scalar | *Visual | NORML | NORML | NORML |
| Odor | scalar | *Visual | NORML | NORML | NORML |
| Emulsified Water | scalar | *Visual | >0.2 | NEG | NEG |
| Free Water | scalar | *Visual | | NEG | NEG |

| FLUID PROPERTIES | method | limit/base | current | history1 | history2 | |
|------------------|--------|------------|---------|-------------|----------|------|
| Visc @ 100°C | cSt | ASTM D445 | 15.4 | 14.4 | 13.7 | 14.2 |

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0104435 **Received** : 19 Mar 2024
Lab Number : **06122114** **Tested** : 26 Mar 2024
Unique Number : 10936265 **Diagnosed** : 26 Mar 2024 - Jonathan Hester
Test Package : FLEET

GFL Environmental - 410 - Michigan West
 39000 Van Born Rd
 Wayne, MI
 US 48184
 Contact: Jennifer Shurko
 jshurko@gflenv.com
 T: (734)714-2340
 F:

Certificate L2367
 To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)