




# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Machine Id  
**140M**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**



## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>GFL0114324</b>	GFL0069900	GFL0069874
Sample Date	Client Info		<b>15 Mar 2024</b>	17 May 2023	09 May 2023
Machine Age	hrs	Client Info	<b>16348</b>	0	14869
Oil Age	hrs	Client Info	<b>0</b>	0	600
Oil Changed	Client Info		<b>Changed</b>	Changed	Changed
Sample Status			<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >120	<b>9</b>	19	2
Chromium	ppm	ASTM D5185m >20	<b>&lt;1</b>	1	<1
Nickel	ppm	ASTM D5185m >5	<b>&lt;1</b>	0	0
Titanium	ppm	ASTM D5185m >2	<b>&lt;1</b>	0	0
Silver	ppm	ASTM D5185m >2	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m >20	<b>2</b>	5	1
Lead	ppm	ASTM D5185m >40	<b>2</b>	0	0
Copper	ppm	ASTM D5185m >330	<b>2</b>	<1	0
Tin	ppm	ASTM D5185m >15	<b>&lt;1</b>	<1	<1
Vanadium	ppm	ASTM D5185m	<b>0</b>	0	0
Cadmium	ppm	ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	<b>2</b>	4	6
Barium	ppm	ASTM D5185m 0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m 60	<b>59</b>	57	59
Manganese	ppm	ASTM D5185m 0	<b>0</b>	<1	<1
Magnesium	ppm	ASTM D5185m 1010	<b>935</b>	935	945
Calcium	ppm	ASTM D5185m 1070	<b>1092</b>	1026	1070
Phosphorus	ppm	ASTM D5185m 1150	<b>1023</b>	1004	1048
Zinc	ppm	ASTM D5185m 1270	<b>1267</b>	1237	1256
Sulfur	ppm	ASTM D5185m 2060	<b>3099</b>	3478	3780

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<b>4</b>	4	3
Sodium	ppm	ASTM D5185m	<b>4</b>	1	2
Potassium	ppm	ASTM D5185m >20	<b>3</b>	6	<1

## INFRA-RED



	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >4	<b>0.4</b>	0.5	0.1
Nitration	Abs/cm	*ASTM D7624 >20	<b>8.9</b>	8.5	5.9
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>20.0</b>	19.6	17.8

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>17.2</b>	15.3	13.8
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	<b>6.9</b>	8.5	7.1







# OIL ANALYSIS REPORT



PARAMETER	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	13.5	13.7

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0114324 **Received** : 19 Mar 2024  
**Lab Number** : 06122138 **Tested** : 20 Mar 2024  
**Unique Number** : 10936289 **Diagnosed** : 20 Mar 2024 - Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 468 - Dearborn**  
 3051 Schaefer Rd  
 Dearborn, MI  
 US 48126  
 Contact:

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: