

OIL ANALYSIS REPORT

No Info On Sample Machine Id [No Info On Sample] NOT GIVEN PCA0106545 Component

Diesel Engine

PETRO CANADA DURON SHP 10W30 (--- GAL)

DIAGNOSIS

Recommendation

Oil and filter change at the time of sampling has been noted. No corrective action is recommended at this time. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

Elevated aluminum (AI) and/or lead (Pb) and potassium (K) levels in your metals analysis are likely a result of solder flux release into the lubricant and is common on new equipment/components. No other contaminants were detected in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is acceptable for the time in service.

GAL)				Mar2024		
SAMPLE INFOR	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0106545		
Sample Date		Client Info		13 Mar 2024		
Machine Age	mls	Client Info		81000		
Oil Age	mls	Client Info		81000		
Oil Changed	IIIIO	Client Info		Changed		
Sample Status				NORMAL		
CONTAMINAT	ION	method	limit/base	current	history1	history2
Fuel		WC Method	>5	<1.0		
Water		WC Method		NEG		
Glycol		WC Method	, 0.1	NEG		
-	0		limit/base	-	history	biotory ()
WEAR METAL		method		current	history1	history2
Iron	ppm	ASTM D5185m	>100	85		
Chromium	ppm	ASTM D5185m	>20	8		
Nickel	ppm	ASTM D5185m	>4	<1		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m	>3	0		
Aluminum	ppm	ASTM D5185m	>20	173		
Lead	ppm	ASTM D5185m	>40	1		
Copper	ppm	ASTM D5185m	>330	169		
Tin	ppm	ASTM D5185m	>15	4		
Vanadium	ppm	ASTM D5185m		<1		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	2	21		
Barium	ppm	ASTM D5185m		<1		
Molybdenum	ppm	ASTM D5185m	50	42		
Manganese	ppm	ASTM D5185m		5		
Magnesium	ppm	ASTM D5185m	950	544		
Calcium	ppm	ASTM D5185m	1050	1682		
Phosphorus	ppm	ASTM D5185m	995	716		
Zinc	ppm	ASTM D5185m		854		
Sulfur	ppm	ASTM D5185m	2600	2022		
CONTAMINAN	ITS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	9		
Sodium	ppm	ASTM D5185m		9		
Potassium	ppm	ASTM D5185m	>20	385		
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	0.9		
Nitration	Abs/cm	*ASTM D7624	>20	13.0		
Sulfation	Abs/.1mm	*ASTM D7415	>30	25.3		
FLUID DEGRA	DATION	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	29.9		
Base Number (BN)	mg KOH/g	ASTM D2896		4.6		



Sample Rating Trend



NORMAL



OIL ANALYSIS REPORT

