


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id **407** Component

Diesel Engine

RED GIANT LOCOMOTIVE EO 20W40 (--- 0

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the


Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

| AL) | | | Dec2023 | Mar2024 | | |
|------------------|----------|-------------|------------|-------------|-------------|----------|
| SAMPLE INFOR | MATION | method | limit/base | current | history1 | history2 |
| Sample Number | | Client Info | | PCA0092769 | PCA0092752 | |
| Sample Date | | Client Info | | 11 Mar 2024 | 11 Dec 2023 | |
| Machine Age | hrs | Client Info | | 0 | 0 | |
| Oil Age | hrs | Client Info | | 0 | 0 | |
| Oil Changed | | Client Info | | N/A | N/A | |
| Sample Status | | | | NORMAL | NORMAL | |
| CONTAMINAT | ION | method | limit/base | current | history1 | history2 |
| uel | | WC Method | >4 | <1.0 | <1.0 | |
| Vater | | WC Method | >0.20 | NEG | NEG | |
| Glycol | | WC Method | | NEG | NEG | |
| WEAR METAL | .S | method | limit/base | current | history1 | history2 |
| ron | ppm | ASTM D5185m | >100 | 15 | 16 | |
| Chromium | ppm | ASTM D5185m | >15 | 0 | <1 | |
| Nickel | ppm | ASTM D5185m | >5 | 0 | 0 | |
| Γitanium | ppm | ASTM D5185m | | 0 | <1 | |
| Silver | ppm | ASTM D5185m | >2 | 0 | 0 | |
| Aluminum | ppm | ASTM D5185m | >10 | 2 | 2 | |
| _ead | ppm | ASTM D5185m | >75 | 6 | 12 | |
| Copper | ppm | ASTM D5185m | >90 | 4 | 5 | |
| Γin | ppm | ASTM D5185m | >30 | 0 | 2 | |
| /anadium | ppm | ASTM D5185m | | 0 | 0 | |
| Cadmium | ppm | ASTM D5185m | | 0 | 0 | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | | 44 | 45 | |
| Barium | ppm | ASTM D5185m | | 0 | 0 | |
| Molybdenum | ppm | ASTM D5185m | | 45 | 42 | |
| Manganese | ppm | ASTM D5185m | | 0 | <1 | |
| Magnesium | ppm | ASTM D5185m | | 9 | 13 | |
| Calcium | ppm | ASTM D5185m | | 3723 | 3283 | |
| Phosphorus | ppm | ASTM D5185m | 0 | 0 | 3 | |
| Zinc | ppm | ASTM D5185m | 0 | 0 | 0 | |
| Sulfur | ppm | ASTM D5185m | 1900 | 3724 | 2865 | |
| CONTAMINAN | ITS | method | limit/base | current | history1 | history2 |
| Silicon | ppm | | >17 | 7 | 9 | |
| Sodium | ppm | ASTM D5185m | | 33 | 36 | |
| Potassium | ppm | ASTM D5185m | >20 | 0 | <1 | |
| INFRA-RED | | method | limit/base | current | history1 | history2 |
| Soot % | % | *ASTM D7844 | >3 | 0.4 | 0.5 | |
| Nitration | Abs/cm | *ASTM D7624 | >20 | 7.7 | 7.5 | |
| Sulfation | Abs/.1mm | *ASTM D7415 | >30 | 15.4 | 15.9 | |
| FLUID DEGRA | DATION | method | limit/base | current | history1 | history2 |
| Oxidation | Abs/.1mm | *ASTM D7414 | >25 | 6.9 | 7.0 | |
| Base Number (BN) | mg KOH/g | ASTM D2896 | 11 | 9.67 | 10.00 | |



OIL ANALYSIS REPORT



| VISUAL | | method | limit/base | current | history1 | history2 |
|-------------------------|--------|-----------|------------|---------|----------|----------|
| White Metal | scalar | *Visual | NONE | NONE | NONE | |
| Yellow Metal | scalar | *Visual | NONE | NONE | NONE | |
| Precipitate | scalar | *Visual | NONE | NONE | NONE | |
| Silt | scalar | *Visual | NONE | NONE | NONE | |
| Debris | scalar | *Visual | NONE | NONE | NONE | |
| Sand/Dirt | scalar | *Visual | NONE | NONE | NONE | |
| Appearance | scalar | *Visual | NORML | NORML | NORML | |
| Odor | scalar | *Visual | NORML | NORML | NORML | |
| Emulsified Water | scalar | *Visual | >0.20 | NEG | NEG | |
| Free Water | scalar | *Visual | | NEG | NEG | |
| FLUID PROPE | RTIES | method | limit/base | current | history1 | history2 |
| Visc @ 100°C | cSt | ASTM D445 | 15.4 | 15.1 | 15.3 | |

| 130 @ 100 O COL AC | 7 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | |
|--------------------|---|---|
| GRAPHS | | |
| Iron (ppm) | Lead (| [ppm] |
| Severe | 100 Severe 80 Change | |
| Abnormal | 00 | |
| | Edd 40 | |
| | 20 | |
| £23 | 23 0 24 | |
| Dec11/23 | Mari 1,24 | |
| Aluminum (ppm) | | nium (ppm) |
| Severe | 25 7 | |
| Abnormal | Abnormal | I |
| | E 10 | |
| | 5 | |
| r: | 25 0 50 | |
| Dec11/23 | Mar11,24 | |
| Copper (ppm) | | (ppm) |
| Severe | 25 T Severe | |
| Abnormal | Abnormal | |
| | E 10 | |
| 1 | 5 | |
| 33 | 0 | |
| Dec11/23 | Mari 1,24 | |
| Viscosity @ 100°C | | Number |
| 17 | 12 O T Page | *************************************** |
| Severe Abnormal | W KO | |
| Base | Abnormal | l |
| Abgagmal B | Abnormal August Mark Mark Mark Mark Mark Mark Mark Mark | |
| Li | | |
| Dec11/23 | Mari1,/24 | |



Certificate L2367

Laboratory

Sample No. : PCA0092769 Lab Number : 06123882 Unique Number : 10938033 Test Package : MOB 2

: WearCheck USA - 501 Madison Ave., Cary, NC 27513

Received : 20 Mar 2024 Tested Diagnosed

: 21 Mar 2024 : 21 Mar 2024 - Wes Davis

U.S. SUGAR CORP 1731 S W.C. OWEN AVENUE CLEWISTON, FL US 33440-3032

Contact: JAMES MCGROGAN jmcgrogan@ussugar.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:

F: