


# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**


Area  
**Walgreens - Tractor**  
 Machine for  
**[Walgreens - Tractor] 136A63371**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 10W30 (11 GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

Metal levels are typical for a new component breaking in.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>PCA0117879</b>	PCA0105453	---
Sample Date	Client Info		<b>12 Mar 2024</b>	27 Dec 2023	---
Machine Age	mls	Client Info	<b>62131</b>	37646	---
Oil Age	mls	Client Info	<b>25000</b>	37646	---
Oil Changed	Client Info		<b>Not Changed</b>	Changed	---
Sample Status			<b>NORMAL</b>	NORMAL	---

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>2.0	<b>&lt;1.0</b>	<1.0	---
Water	WC Method	>0.2	<b>NEG</b>	NEG	---
Glycol	WC Method		<b>NEG</b>	NEG	---

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >100	<b>24</b>	55	---
Chromium	ppm	ASTM D5185m >20	<b>&lt;1</b>	<1	---
Nickel	ppm	ASTM D5185m >4	<b>2</b>	<1	---
Titanium	ppm	ASTM D5185m	<b>0</b>	0	---
Silver	ppm	ASTM D5185m >3	<b>&lt;1</b>	0	---
Aluminum	ppm	ASTM D5185m >20	<b>6</b>	12	---
Lead	ppm	ASTM D5185m >40	<b>4</b>	6	---
Copper	ppm	ASTM D5185m >330	<b>7</b>	19	---
Tin	ppm	ASTM D5185m >15	<b>2</b>	4	---
Vanadium	ppm	ASTM D5185m	<b>0</b>	0	---
Cadmium	ppm	ASTM D5185m	<b>0</b>	0	---

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 2	<b>10</b>	25	---
Barium	ppm	ASTM D5185m 0	<b>&lt;1</b>	4	---
Molybdenum	ppm	ASTM D5185m 50	<b>58</b>	62	---
Manganese	ppm	ASTM D5185m 0	<b>2</b>	4	---
Magnesium	ppm	ASTM D5185m 950	<b>816</b>	471	---
Calcium	ppm	ASTM D5185m 1050	<b>1216</b>	1741	---
Phosphorus	ppm	ASTM D5185m 995	<b>1012</b>	949	---
Zinc	ppm	ASTM D5185m 1180	<b>1266</b>	1263	---
Sulfur	ppm	ASTM D5185m 2600	<b>3341</b>	2765	---

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<b>13</b>	40	---
Sodium	ppm	ASTM D5185m	<b>2</b>	4	---
Potassium	ppm	ASTM D5185m >20	<b>9</b>	22	---



## INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	<b>0.4</b>	0.6	---
Nitration	Abs/cm	*ASTM D7624 >20	<b>8.3</b>	10.0	---
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>20.4</b>	23.4	---

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>16.7</b>	21.0	---
Base Number (BN)	mg KOH/g	ASTM D2896	<b>7.3</b>	5.7	---





# OIL ANALYSIS REPORT



PARAMETER	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	12.00	<b>11.5</b>	11.5

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0117879  
**Lab Number** : **06124247**  
**Unique Number** : 10938398  
**Test Package** : FLEET

**Received** : 20 Mar 2024  
**Tested** : 21 Mar 2024  
**Diagnosed** : 21 Mar 2024 - Wes Davis

**Transervice - Shop 1366 - Berkeley-Woodland**  
 2370 East Main Street  
 Woodland, CA  
 US 95776  
 Contact: Gary Mann  
 gmann@transervice.com  
 T: (530)666-7771  
 F: (530)406-7971

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)