


OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Area
MESCO
 Machine Id
111032
 Component
Diesel Engine
 Fluid
PETRO CANADA DURON SHP 10W30 (--- QTS)



DIAGNOSIS

Recommendation
 Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

Wear
 All component wear rates are normal.

Contamination
 There is no indication of any contamination in the oil.

Fluid Condition
 The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	PCA0116931	PCA0105829	PCA0105755
Sample Date	Client Info	01 Mar 2024	18 Jan 2024	14 Nov 2023
Machine Age	mls Client Info	110773	103668	94532
Oil Age	mls Client Info	0	0	0
Oil Changed	Client Info	Changed	N/A	Changed
Sample Status		NORMAL	---	NORMAL

CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<1.0	<1.0	<1.0
Water	WC Method >0.2	NEG	NEG	NEG
Glycol	WC Method	NEG	NEG	NEG

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >100	17	---	31
Chromium	ppm ASTM D5185m >20	<1	---	1
Nickel	ppm ASTM D5185m >4	0	---	0
Titanium	ppm ASTM D5185m	<1	---	0
Silver	ppm ASTM D5185m >3	<1	---	0
Aluminum	ppm ASTM D5185m >20	3	---	2
Lead	ppm ASTM D5185m >40	<1	---	0
Copper	ppm ASTM D5185m >330	9	---	0
Tin	ppm ASTM D5185m >15	<1	---	0
Vanadium	ppm ASTM D5185m	<1	---	0
Cadmium	ppm ASTM D5185m	0	---	0

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 2	2	---	5
Barium	ppm ASTM D5185m 0	2	---	4
Molybdenum	ppm ASTM D5185m 50	61	---	78
Manganese	ppm ASTM D5185m 0	<1	---	0
Magnesium	ppm ASTM D5185m 950	923	---	1052
Calcium	ppm ASTM D5185m 1050	1143	---	1415
Phosphorus	ppm ASTM D5185m 995	1063	---	1296
Zinc	ppm ASTM D5185m 1180	1226	---	1469
Sulfur	ppm ASTM D5185m 2600	3424	---	4508

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	4	---	0
Sodium	ppm ASTM D5185m	0	---	0
Potassium	ppm ASTM D5185m >20	3	---	0



INFRA-RED

method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	0.7	1.1	1.2
Nitration	Abs/cm *ASTM D7624 >20	8.0	9.9	9.4
Sulfation	Abs/.1mm *ASTM D7415 >30	19.1	19.6	20.1

FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	14.8	15.9	15.6
Base Number (BN)	mg KOH/g ASTM D2896	9.1	9.1	9.6









OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	12.00	11.4	---	11.6

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0116931 **Received** : 21 Mar 2024
Lab Number : 06124528 **Tested** : 21 Mar 2024
Unique Number : 10938679 **Diagnosed** : 21 Mar 2024 - Wes Davis
Test Package : MOB 1 (Additional Tests: TBN)

MILLER TRUCK LEASING #114
 63 REPAUPO STATION ROAD
 LOGAN TOWNSHIP, NJ
 US 08085
 Contact: ED DAVIS
 edavis@millertransgroup.com
 T: (856)214-3521
 F: (856)214-3663

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)