




OIL ANALYSIS REPORT

Sample Rating Trend



WEAR



Area
(EDB493)
Machine Id
3709C
Component
Natural Gas Engine
Fluid
PETRO CANADA DURON SHP 15W40 (8 GAL)

DIAGNOSIS

▲ Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor.

▲ Wear

Cylinder, crank, or cam shaft wear is indicated. All other component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	GFL0111542	GFL0083162	GFL0083178
Sample Date	Client Info	12 Mar 2024	15 Jun 2023	24 May 2023
Machine Age	hrs	Client Info	0	0
Oil Age	hrs	Client Info	0	0
Oil Changed	Client Info	N/A	Not Chngd	N/A
Sample Status		ABNORMAL	NORMAL	NORMAL

CONTAMINATION

method	limit/base	current	history1	history2
Water	WC Method >0.1	NEG	NEG	NEG

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >50	▲ 53	12	19
Chromium	ppm ASTM D5185m >4	3	2	2
Nickel	ppm ASTM D5185m >2	1	<1	1
Titanium	ppm ASTM D5185m	<1	<1	<1
Silver	ppm ASTM D5185m >3	<1	0	<1
Aluminum	ppm ASTM D5185m >9	5	6	6
Lead	ppm ASTM D5185m >30	<1	2	3
Copper	ppm ASTM D5185m >35	3	13	24
Tin	ppm ASTM D5185m >4	<1	<1	1
Vanadium	ppm ASTM D5185m	<1	<1	0
Cadmium	ppm ASTM D5185m	0	<1	0

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	3	3	5
Barium	ppm ASTM D5185m 0	2	0	0
Molybdenum	ppm ASTM D5185m 60	65	60	64
Manganese	ppm ASTM D5185m 0	<1	1	2
Magnesium	ppm ASTM D5185m 1010	968	598	609
Calcium	ppm ASTM D5185m 1070	1217	1701	1688
Phosphorus	ppm ASTM D5185m 1150	1080	689	699
Zinc	ppm ASTM D5185m 1270	1297	994	1013
Sulfur	ppm ASTM D5185m 2060	3398	2824	2732

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >+100	9	4	5
Sodium	ppm ASTM D5185m	4	4	11
Potassium	ppm ASTM D5185m >20	2	1	3

INFRA-RED

method	limit/base	current	history1	history2
Soot %	% *ASTM D7844	2.9	0.1	0.1
Nitration	Abs/cm *ASTM D7624 >20	9.9	11.6	11.0
Sulfation	Abs/.1mm *ASTM D7415 >30	23.7	23.7	22.7


FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	15.7	20.0	19.6
Base Number (BN)	mg KOH/g ASTM D2896 9.8	7.8	3.8	4.2




OIL ANALYSIS REPORT


▲ Ferrous Alloys



Base Number



Viscosity @ 100°C




PARAMETER	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG


PARAMETER	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	15.0	14.0

GRAPHS


▲ Ferrous Alloys




Non-ferrous Metals



Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
 Sample No. : GFL0111542
 Lab Number : 06124773
 Unique Number : 10938924
 Test Package : FLEET

Received : 21 Mar 2024
 Tested : 22 Mar 2024
 Diagnosed : 24 Mar 2024 - Don Baldrige

GFL Environmental - 074 - Douglas - Transwaste
 1219 Landfill Road
 Douglas, GA
 US 31533

Contact: CURTIS JACOBS
 CURTIS.JACOBS@GFLENV.COM

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: