


# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Area  
**(89897X) Walgreens - Tractor**  
 Machine Id  
**[Walgreens - Tractor] 136A69044**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 10W30 (11 GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>PCA0112831</b>	PCA0112888	PCA0100236
Sample Date	Client Info	<b>15 Mar 2024</b>	16 Nov 2023	14 Jul 2023
Machine Age	mls Client Info	<b>585768</b>	561774	545023
Oil Age	mls Client Info	<b>23994</b>	56371	13902
Oil Changed	Client Info	<b>Not Changed</b>	Changed	Not Changed
Sample Status		<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<b>&lt;1.0</b>	0.3	<1.0
Water	WC Method >0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method	<b>NEG</b>	NEG	NEG

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >80	<b>14</b>	7	7
Chromium	ppm ASTM D5185m >5	<b>1</b>	<1	<1
Nickel	ppm ASTM D5185m >2	<b>&lt;1</b>	<1	0
Titanium	ppm ASTM D5185m	<b>&lt;1</b>	0	0
Silver	ppm ASTM D5185m >3	<b>0</b>	0	0
Aluminum	ppm ASTM D5185m >30	<b>5</b>	5	4
Lead	ppm ASTM D5185m >30	<b>&lt;1</b>	<1	0
Copper	ppm ASTM D5185m >150	<b>2</b>	1	<1
Tin	ppm ASTM D5185m >5	<b>&lt;1</b>	<1	0
Vanadium	ppm ASTM D5185m	<b>0</b>	0	0
Cadmium	ppm ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 2	<b>0</b>	4	5
Barium	ppm ASTM D5185m 0	<b>0</b>	0	0
Molybdenum	ppm ASTM D5185m 50	<b>65</b>	55	60
Manganese	ppm ASTM D5185m 0	<b>&lt;1</b>	<1	<1
Magnesium	ppm ASTM D5185m 950	<b>989</b>	899	991
Calcium	ppm ASTM D5185m 1050	<b>1127</b>	1059	1159
Phosphorus	ppm ASTM D5185m 995	<b>1004</b>	1080	1088
Zinc	ppm ASTM D5185m 1180	<b>1262</b>	1232	1336
Sulfur	ppm ASTM D5185m 2600	<b>2789</b>	3020	3982

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >20	<b>7</b>	3	3
Sodium	ppm ASTM D5185m	<b>0</b>	2	1
Potassium	ppm ASTM D5185m >20	<b>3</b>	5	2



## INFRA-RED

method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	<b>0.4</b>	0.3	0.2
Nitration	Abs/cm *ASTM D7624 >20	<b>8.1</b>	7.3	6.0
Sulfation	Abs/.1mm *ASTM D7415 >30	<b>19.4</b>	19.6	18.2

## FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	<b>16.0</b>	14.8	13.6
Base Number (BN)	mg KOH/g ASTM D2896	<b>7.8</b>	8.3	8.9





# OIL ANALYSIS REPORT



PARAMETER	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	12.00	11.7	11.4

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0112831  
**Lab Number** : 06126199  
**Unique Number** : 10940350  
**Test Package** : FLEET

**Transervice - Shop 1364 - Berkeley-Mt. Vernon**  
 5100 Lake Terrace NE  
 Mt. Vernon, IL  
 US 62864  
 Contact: Erien White  
 ewhite@transervice.com  
 T: (618)244-8726  
 F: (618)244-8791

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)