

OIL ANALYSIS REPORT

(43-329HA) 710022

Component **Diesel Engine**

DIESEL ENGINE OIL SAE 40 (--- GAL)

Sample Rating Trend



DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.


Fluid Condition


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

		eb2021 May20	21 Jul2021 Nov2021 May2	022 May2023 Oct2023 Dec2023 Ja	n2024 Mar202		
SAMPLE INFORI	MATION	method	limit/base	current	history1	history2	
Sample Number		Client Info		GFL0111893	GFL0111847	GFL0108312	
Sample Date		Client Info		20 Mar 2024	22 Feb 2024	24 Jan 2024	
Machine Age	hrs	Client Info		8578	8454	8279	
Oil Age	hrs	Client Info		8403	175	4046	
Oil Changed		Client Info		Not Changd	Not Changd	Changed	
Sample Status				NORMAL	NORMAL	NORMAL	
CONTAMINAT	ION	method	limit/base	current	history1	history2	
Fuel		WC Method	>5	<1.0	<1.0	<1.0	
Water		WC Method	>0.2	NEG	NEG	NEG	
Glycol		WC Method		NEG	NEG	NEG	
WEAR METAL	S	method	limit/base	current	history1	history2	
Iron	ppm	ASTM D5185m	>100	8	5	12	
Chromium	ppm	ASTM D5185m	>20	<1	<1	<1	
Nickel	ppm	ASTM D5185m	>4	<1	0	0	
Titanium	ppm	ASTM D5185m		<1	0	0	
Silver	ppm	ASTM D5185m	>3	<1	0	0	
Aluminum	ppm	ASTM D5185m	>20	5	2	2	
Lead	ppm	ASTM D5185m	>40	4	0	2	
Copper	ppm	ASTM D5185m	>330	1	1	<1	
Tin	ppm	ASTM D5185m	>15	2	0	<1	
Vanadium	ppm	ASTM D5185m		<1	0	0	
Cadmium	ppm	ASTM D5185m		<1	0	0	
ADDITIVES		method	limit/base	current	history1	history2	
Boron	ppm	ASTM D5185m	250	14	13	8	
Barium	ppm	ASTM D5185m	10	1	8	0	
Molybdenum	ppm	ASTM D5185m	100	56	56	58	
Manganese	ppm	ASTM D5185m		<1	0	<1	
Magnesium	ppm	ASTM D5185m	450	894	789	908	
Calcium	ppm	ASTM D5185m	3000	1179	981	1137	
Phosphorus	ppm	ASTM D5185m	1150	1132	889	1025	
Zinc	ppm	ASTM D5185m	1350	1211	1061	1230	
Sulfur	ppm	ASTM D5185m	4250	3328	2838	3025	
CONTAMINAN	TS	method	limit/base	current	history1	history2	
Silicon	ppm	ASTM D5185m	>25	10	4	7	
Sodium	ppm	ASTM D5185m	>216	0	0	2	
Potassium	ppm	ASTM D5185m	>20	4	4	<1	
INFRA-RED		method	limit/base	current	history1	history2	
Soot %	%	*ASTM D7844	>3	0.5	0.4	0.8	
Nitration	Abs/cm	*ASTM D7624	>20	10.3	8.1	12.2	
Sulfation	Abs/.1mm	*ASTM D7415	>30	19.7	19.1	22.4	
FLUID DEGRADATION method limit/base current history1 history2							
Oxidation	Abs/.1mm	*ASTM D7414	>25	18.8	16.1	22.2	
Base Number (BN)	mg KOH/g	ASTM D2896	8.5	7.4	8.0	6.8	
. ,	- 0						



OIL ANALYSIS REPORT








VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG


FLUID PROPERTIES		method				history2
Visc @ 100°C	cSt	ASTM D445	14.4	12.8	13.1	12.4

GRAPHS













Certificate L2367

Laboratory Sample No.

Test Package : FLEET

: GFL0111893 Lab Number : 06126857 Unique Number : 10941008

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 22 Mar 2024 **Tested**

: 26 Mar 2024 Diagnosed : 26 Mar 2024 - Wes Davis

GFL Environmental - 652 - Fredericksburg Hauling

10954 Houser Drive Fredericksburg, VA US 22408

Contact: WILLIAM MILO wmilo@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:

F: