




OIL ANALYSIS REPORT

Sample Rating Trend



GLYCOL



Machine Id
729091

Component
Diesel Engine

Fluid
PETRO CANADA DURON SHP 15W40 (--- GAL)

DIAGNOSIS

Recommendation

We advise that you check for the source of the coolant leak. Check for low coolant level. We recommend an early resample to monitor this condition.

Wear

All component wear rates are normal.

Contamination

Sodium and/or potassium levels remain high.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	GFL0111891	GFL0111832	GFL0108249
Sample Date	Client Info	20 Mar 2024	29 Feb 2024	07 Feb 2024
Machine Age	hrs	Client Info	15330	15189
Oil Age	hrs	Client Info	15330	15189
Oil Changed	Client Info	Not Changed	Not Changed	Not Changed
Sample Status		ABNORMAL	ABNORMAL	ABNORMAL

CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<1.0	<1.0	<1.0
Water	WC Method >0.2	NEG	NEG	NEG

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >100	63	62	48
Chromium	ppm ASTM D5185m >20	2	1	1
Nickel	ppm ASTM D5185m >4	2	1	2
Titanium	ppm ASTM D5185m	<1	0	<1
Silver	ppm ASTM D5185m >3	<1	0	0
Aluminum	ppm ASTM D5185m >20	9	5	4
Lead	ppm ASTM D5185m >40	3	3	<1
Copper	ppm ASTM D5185m >330	11	8	7
Tin	ppm ASTM D5185m >15	2	0	<1
Vanadium	ppm ASTM D5185m	<1	0	<1
Cadmium	ppm ASTM D5185m	<1	0	<1

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	4	2	2
Barium	ppm ASTM D5185m 0	2	0	14
Molybdenum	ppm ASTM D5185m 60	137	119	95
Manganese	ppm ASTM D5185m 0	1	<1	1
Magnesium	ppm ASTM D5185m 1010	932	1031	824
Calcium	ppm ASTM D5185m 1070	1142	1158	1021
Phosphorus	ppm ASTM D5185m 1150	1289	1090	986
Zinc	ppm ASTM D5185m 1270	1267	1313	1112
Sulfur	ppm ASTM D5185m 2060	3492	3406	3421

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	13	6	6
Sodium	ppm ASTM D5185m	▲ 89	▲ 68	▲ 49
Potassium	ppm ASTM D5185m >20	▲ 606	▲ 371	▲ 275
Glycol	% *ASTM D2982	NEG	NEG	NEG

INFRA-RED




method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	0.1	0.1	0.1
Nitration	Abs/cm *ASTM D7624 >20	7.8	7.5	6.4
Sulfation	Abs.1mm *ASTM D7415 >30	18.3	18.0	17.7

FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs.1mm *ASTM D7414 >25	14.7	14.3	13.5
Base Number (BN)	mg KOH/g ASTM D2896 9.8	8.9	9.0	8.7







OIL ANALYSIS REPORT



PARAMETER	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	13.8	13.7

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0111891 **Received** : 22 Mar 2024
Lab Number : 06126862 **Tested** : 27 Mar 2024
Unique Number : 10941013 **Diagnosed** : 27 Mar 2024 - Jonathan Hester
Test Package : FLEET (Additional Tests: Glycol)

GFL Environmental - 652 - Fredericksburg Hauling
 10954 Houser Drive
 Fredericksburg, VA
 US 22408
 Contact: WILLIAM MILO
 wmi@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: