




# PROBLEM SUMMARY

## Sample Rating Trend


FUEL




Area  
**(TX106468)**  
 Machine Id  
**10261**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 15W40 (7 GAL)**

## COMPONENT CONDITION SUMMARY

### Fuel Dilution



### Viscosity @ 100°C



## RECOMMENDATION

We advise that you check the fuel injection system. We recommend that you drain the oil from the component if this has not already been done. We recommend an early resample to monitor this condition.

## PROBLEMATIC TEST RESULTS

Sample Status				SEVERE	SEVERE	NORMAL
Fuel	%	ASTM D3524	>3.0	▲ 7.1	▲ 7.1	<1.0
Visc @ 100°C	cSt	ASTM D445	15.4	▲ 12.3	▲ 12.0	13.3

Customer Id: GFL045  
 Sample No.: GFL0112168  
 Lab Number: 06127504  
 Test Package: FLEET



To manage this report scan the QR code

To discuss the diagnosis or test data:  
 Wes Davis +1 905-569-8600 x223  
[wesd@wearcheck.ca](mailto:wesd@wearcheck.ca)

To change component or sample information:  
 Customer Service +1 1-800-237-1369  
[customerservice@wearcheck.com](mailto:customerservice@wearcheck.com)

## RECOMMENDED ACTIONS

Action	Status	Date	Done By	Description
Change Fluid	---	---	?	We recommend that you drain the oil from the component if this has not already been done.
Resample	---	---	?	We recommend an early resample to monitor this condition.
Check Fuel/injector System	---	---	?	We advise that you check the fuel injection system.

## HISTORICAL DIAGNOSIS

### FUEL



#### 08 Feb 2024 Diag: Wes Davis

We advise that you check the fuel injection system. We recommend that you drain the oil from the component if this has not already been done. We recommend an early resample to monitor this condition. All component wear rates are normal. There is a high amount of fuel present in the oil. Tests confirm the presence of fuel in the oil. The BN result indicates that there is suitable alkalinity remaining in the oil. Fuel is present in the oil and is lowering the viscosity. The oil is no longer serviceable due to the presence of contaminants.

view report



### NORMAL



#### 04 Apr 2023 Diag: Angela Borella

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

view report



### NORMAL



#### 06 Dec 2022 Diag: Don Baldrige

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.


view report





# OIL ANALYSIS REPORT

Sample Rating Trend



FUEL



Area  
**(TX106468)**  
Machine Id  
**10261**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 15W40 (7 GAL)**

## DIAGNOSIS

### Recommendation

We advise that you check the fuel injection system. We recommend that you drain the oil from the component if this has not already been done. We recommend an early resample to monitor this condition.

### Wear

All component wear rates are normal.

### Contamination

There is a high amount of fuel present in the oil. Tests confirm the presence of fuel in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. Fuel is present in the oil and is lowering the viscosity. The oil is no longer serviceable due to the presence of contaminants.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>GFL0112168</b>	GFL0112133	GFL0052205
Sample Date	Client Info	<b>18 Mar 2024</b>	08 Feb 2024	04 Apr 2023
Machine Age	hrs	<b>85103</b>	85103	85103
Oil Age	hrs	<b>85103</b>	85103	0
Oil Changed	Client Info	<b>N/A</b>	N/A	Changed
Sample Status		<b>SEVERE</b>	SEVERE	NORMAL

## CONTAMINATION

method	limit/base	current	history1	history2
Water	WC Method >0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method	<b>NEG</b>	NEG	NEG

## WEAR METALS

method	limit/base	current	history1	history2	
Iron	ppm	ASTM D5185m >90	<b>29</b>	21	86
Chromium	ppm	ASTM D5185m >20	<b>2</b>	1	5
Nickel	ppm	ASTM D5185m >2	<b>2</b>	0	2
Titanium	ppm	ASTM D5185m >2	<b>&lt;1</b>	0	0
Silver	ppm	ASTM D5185m >2	<b>&lt;1</b>	0	0
Aluminum	ppm	ASTM D5185m >20	<b>4</b>	4	7
Lead	ppm	ASTM D5185m >40	<b>&lt;1</b>	0	<1
Copper	ppm	ASTM D5185m >330	<b>3</b>	<1	2
Tin	ppm	ASTM D5185m >15	<b>1</b>	0	<1
Vanadium	ppm	ASTM D5185m	<b>&lt;1</b>	0	<1
Cadmium	ppm	ASTM D5185m	<b>&lt;1</b>	0	0

## ADDITIVES

method	limit/base	current	history1	history2	
Boron	ppm	ASTM D5185m 0	<b>9</b>	13	2
Barium	ppm	ASTM D5185m 0	<b>1</b>	0	0
Molybdenum	ppm	ASTM D5185m 60	<b>59</b>	58	91
Manganese	ppm	ASTM D5185m 0	<b>1</b>	<1	1
Magnesium	ppm	ASTM D5185m 1010	<b>847</b>	888	1438
Calcium	ppm	ASTM D5185m 1070	<b>1042</b>	1004	1600
Phosphorus	ppm	ASTM D5185m 1150	<b>950</b>	1008	1482
Zinc	ppm	ASTM D5185m 1270	<b>1141</b>	1185	1913
Sulfur	ppm	ASTM D5185m 2060	<b>2846</b>	2753	3891

## CONTAMINANTS

method	limit/base	current	history1	history2	
Silicon	ppm	ASTM D5185m >25	<b>9</b>	6	20
Sodium	ppm	ASTM D5185m	<b>3</b>	5	15
Potassium	ppm	ASTM D5185m >20	<b>5</b>	0	3
Fuel	%	ASTM D3524 >3.0	<b>▲ 7.1</b>	▲ 7.1	<1.0

## INFRA-RED





method	limit/base	current	history1	history2	
Soot %	%	*ASTM D7844 >6	<b>0.3</b>	0.3	1.4
Nitration	Abs/cm	*ASTM D7624 >20	<b>9.4</b>	8.4	14.2
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>19.8</b>	19.4	26.1

## FLUID DEGRADATION

method	limit/base	current	history1	history2	
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>18.1</b>	16.8	27.6
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	<b>8.3</b>	8.4	7.3







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	▲ 12.3	▲ 12.0

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0112168 **Received** : 25 Mar 2024  
**Lab Number** : 06127504 **Tested** : 27 Mar 2024  
**Unique Number** : 10941655 **Diagnosed** : 27 Mar 2024 - Wes Davis  
**Test Package** : FLEET ( Additional Tests: PercentFuel )

**GFL Environmental - 045 - Tidewater**  
 3821 Cook Blvd.  
 Chesapeake, VA  
 US 23323  
 Contact: ELVIN RODRIGUEZ  
 elvinrodriguez@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)