


Machine Id
SENNEBOGEN 835 MH-76

Component
Diesel Engine

Fluid
PETRO CANADA DURON HP 15W40 (--- LTR)



DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			PCA0113892	PCA0083692	PCA0083684
Sample Date	Client Info			14 Mar 2024	10 Feb 2023	03 Jan 2023
Machine Age	hrs	Client Info		21270	17332	11139
Oil Age	hrs	Client Info		500	500	500
Oil Changed	Client Info			Changed	Changed	Changed
Sample Status				NORMAL	SEVERE	SEVERE

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>5		<1.0	<1.0	<1.0
Water	WC Method	>0.2		NEG	NEG	NEG
Glycol	WC Method			NEG	NEG	NEG

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	88	62	▲ 176
Chromium	ppm	ASTM D5185m	>20	6	4	6
Nickel	ppm	ASTM D5185m	>4	2	<1	3
Titanium	ppm	ASTM D5185m		<1	0	<1
Silver	ppm	ASTM D5185m	>3	<1	0	0
Aluminum	ppm	ASTM D5185m	>20	9	3	5
Lead	ppm	ASTM D5185m	>40	<1	1	2
Copper	ppm	ASTM D5185m	>330	10	2	5
Tin	ppm	ASTM D5185m	>15	1	<1	<1
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0



ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		7	3	4
Barium	ppm	ASTM D5185m		0	0	12
Molybdenum	ppm	ASTM D5185m		64	58	52
Manganese	ppm	ASTM D5185m		1	<1	2
Magnesium	ppm	ASTM D5185m		993	863	756
Calcium	ppm	ASTM D5185m		1103	1043	906
Phosphorus	ppm	ASTM D5185m		1036	948	808
Zinc	ppm	ASTM D5185m		1312	1150	973
Sulfur	ppm	ASTM D5185m		3256	2857	2387

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	8	5	10
Sodium	ppm	ASTM D5185m		8	<1	4
Potassium	ppm	ASTM D5185m	>20	3	2	0

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	0.6	▲ 7.2	▲ 8.5
Nitration	Abs/cm	*ASTM D7624	>20	13.3	22.4	34.6
Sulfation	Abs/.1mm	*ASTM D7415	>30	23.7	40.2	67.8

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	23.1	31.3	57.8
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	7.73	10.65	7.95









OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2	
White Metal	scalar	*Visual	NONE	LIGHT	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.6	12.6	▲ 19.3	▲ 38.1

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0113892 **Received** : 26 Mar 2024
Lab Number : **06129570** **Tested** : 27 Mar 2024
Unique Number : 10943721 **Diagnosed** : 27 Mar 2024 - Wes Davis
Test Package : MOB 2

SCRAP METAL SERVICES (SMS Mill Services LLC)
 250 WEST U.S. HWY 12
 CHESTERTON, IN
 US 46304
 Contact: WALTER MURRAY
 wmurray@scrapmetalservices.com
 T: (219)787-1341
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)