




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Area  
**(DUX471)**  
Machine Id  
**10669**  
Component  
**Transmission (Auto)**  
Fluid  
**PETRO CANADA DuraDrive HD Synthetic 668 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the fluid.

### Fluid Condition

The condition of the fluid is acceptable for the time in service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>GFL0115763</b>	GFL0112380	GFL0107173
Sample Date	Client Info	<b>22 Mar 2024</b>	21 Feb 2024	21 Jan 2024
Machine Age	hrs	<b>73720</b>	50578	50438
Oil Age	hrs	<b>654</b>	583	443
Oil Changed	Client Info	<b>Not Chngd</b>	Not Chngd	Not Chngd
Sample Status		<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

method	limit/base	current	history1	history2
Water	WC Method >0.1	<b>NEG</b>	NEG	NEG

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >160	<b>63</b>	62	62
Chromium	ppm ASTM D5185m >5	<b>0</b>	0	<1
Nickel	ppm ASTM D5185m >5	<b>0</b>	0	<1
Titanium	ppm ASTM D5185m	<b>0</b>	0	<1
Silver	ppm ASTM D5185m >5	<b>0</b>	0	0
Aluminum	ppm ASTM D5185m >50	<b>5</b>	5	3
Lead	ppm ASTM D5185m >50	<b>0</b>	<1	<1
Copper	ppm ASTM D5185m >225	<b>3</b>	4	4
Tin	ppm ASTM D5185m >10	<b>&lt;1</b>	0	<1
Vanadium	ppm ASTM D5185m	<b>0</b>	<1	0
Cadmium	ppm ASTM D5185m	<b>0</b>	0	<1

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m	<b>66</b>	87	76
Barium	ppm ASTM D5185m	<b>0</b>	0	0
Molybdenum	ppm ASTM D5185m	<b>0</b>	0	<1
Manganese	ppm ASTM D5185m	<b>&lt;1</b>	<1	<1
Magnesium	ppm ASTM D5185m	<b>1</b>	0	2
Calcium	ppm ASTM D5185m	<b>118</b>	125	120
Phosphorus	ppm ASTM D5185m	<b>219</b>	209	229
Zinc	ppm ASTM D5185m	<b>3</b>	<1	0
Sulfur	ppm ASTM D5185m	<b>1948</b>	1502	1854

## CONTAMINANTS


method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >20	<b>8</b>	8	9
Sodium	ppm ASTM D5185m	<b>4</b>	4	0
Potassium	ppm ASTM D5185m >20	<b>1</b>	0	2

## VISUAL

method	limit/base	current	history1	history2
White Metal	scalar *Visual	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar *Visual	<b>NONE</b>	NONE	NONE
Precipitate	scalar *Visual	<b>NONE</b>	NONE	NONE
Silt	scalar *Visual	<b>NONE</b>	NONE	NONE
Debris	scalar *Visual	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar *Visual	<b>NONE</b>	NONE	NONE
Appearance	scalar *Visual	<b>NORML</b>	NORML	NORML
Odor	scalar *Visual	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar *Visual	<b>NEG</b>	NEG	NEG
Free Water	scalar *Visual	<b>NEG</b>	NEG	NEG



# OIL ANALYSIS REPORT






### FLUID PROPERTIES

method	limit/base	current	history1	history2
Visc @ 40°C	cSt ASTM D445 34	<b>33.3</b>	33.3	33.6

### SAMPLE IMAGES

method	limit/base	current	history1	history2
Color		no image	no image	no image
Bottom		no image	no image	no image

### GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0115763  
**Lab Number** : 06129685  
**Unique Number** : 10943836  
**Test Package** : FLEET

**Received** : 26 Mar 2024  
**Tested** : 27 Mar 2024  
**Diagnosed** : 27 Mar 2024 - Wes Davis

**GFL Environmental - 010 - Stockbridge**  
 1280 Rum Creek Parkway  
 Stockbridge, GA  
 US 30281  
 Contact: JOSHUA TINKER  
 joshuatinker@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: