




# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Area  
**{UNASSIGNED}**  
 Machine Id  
**933045**  
 Component  
**Transmission (Auto)**  
 Fluid  
**PETRO CANADA DuraDrive HD Synthetic 668 (8 GAL)**



## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the fluid.

### Fluid Condition

The condition of the fluid is acceptable for the time in service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>GFL0115711</b>	GFL0112287	GFL0109948
Sample Date	Client Info	<b>25 Mar 2024</b>	20 Feb 2024	02 Feb 2024
Machine Age	hrs	<b>2490</b>	2167	2022
Oil Age	hrs	<b>135</b>	2167	2022
Oil Changed	Client Info	<b>Not Chngd</b>	Not Chngd	Not Chngd
Sample Status		<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

method	limit/base	current	history1	history2
Water	WC Method >0.1	<b>NEG</b>	NEG	NEG

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >220	<b>33</b>	75	79
Chromium	ppm ASTM D5185m >2	<b>0</b>	<1	<1
Nickel	ppm ASTM D5185m >5	<b>&lt;1</b>	0	0
Titanium	ppm ASTM D5185m	<b>0</b>	0	0
Silver	ppm ASTM D5185m >5	<b>0</b>	0	0
Aluminum	ppm ASTM D5185m >75	<b>11</b>	20	19
Lead	ppm ASTM D5185m >95	<b>5</b>	11	9
Copper	ppm ASTM D5185m >60	<b>8</b>	17	18
Tin	ppm ASTM D5185m >10	<b>2</b>	4	2
Vanadium	ppm ASTM D5185m	<b>0</b>	0	0
Cadmium	ppm ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m	<b>55</b>	45	47
Barium	ppm ASTM D5185m	<b>0</b>	0	6
Molybdenum	ppm ASTM D5185m	<b>0</b>	<1	0
Manganese	ppm ASTM D5185m	<b>&lt;1</b>	2	<1
Magnesium	ppm ASTM D5185m	<b>&lt;1</b>	0	<1
Calcium	ppm ASTM D5185m	<b>114</b>	112	115
Phosphorus	ppm ASTM D5185m	<b>207</b>	193	192
Zinc	ppm ASTM D5185m	<b>7</b>	21	18
Sulfur	ppm ASTM D5185m	<b>1863</b>	1552	1574

## CONTAMINANTS


method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	<b>4</b>	5	4
Sodium	ppm ASTM D5185m	<b>5</b>	6	0
Potassium	ppm ASTM D5185m >20	<b>2</b>	<1	4

## VISUAL

method	limit/base	current	history1	history2
White Metal	scalar *Visual NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar *Visual NONE	<b>NONE</b>	NONE	NONE
Precipitate	scalar *Visual NONE	<b>NONE</b>	NONE	NONE
Silt	scalar *Visual NONE	<b>NONE</b>	NONE	NONE
Debris	scalar *Visual NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar *Visual NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar *Visual NORML	<b>NORML</b>	NORML	NORML
Odor	scalar *Visual NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar *Visual >0.1	<b>NEG</b>	NEG	NEG
Free Water	scalar *Visual	<b>NEG</b>	NEG	NEG



# OIL ANALYSIS REPORT






## FLUID PROPERTIES

method	limit/base	current	history1	history2	
Visc @ 40°C	cSt ASTM D445	34	<b>32.8</b>	33.2	31.9

## SAMPLE IMAGES

method	limit/base	current	history1	history2	
Color			no image	no image	no image
Bottom			no image	no image	no image

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0115711  
**Lab Number** : **06129688**  
**Unique Number** : 10943839  
**Test Package** : FLEET

**Received** : 26 Mar 2024  
**Tested** : 27 Mar 2024  
**Diagnosed** : 27 Mar 2024 - Wes Davis

**GFL Environmental - 010 - Stockbridge**  
 1280 Rum Creek Parkway  
 Stockbridge, GA  
 US 30281  
 Contact: JOSHUA TINKER  
 joshuatinker@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: