

## **OIL ANALYSIS REPORT**

### Sample Rating Trend

# OSHKOSH MIXER 283 (S/N S S

**Diesel Engine** 

{not provided} (--- GAL)

## **DIAGNOSIS**

### Recommendation

We advise that you check the fuel injection system. The oil change at the time of sampling has been noted. We recommend an early resample to monitor this condition. Please specify the brand, type, and viscosity of the oil on your next sample.

All component wear rates are normal.

### ▲ Contamination

There is a high amount of fuel present in the oil. Tests confirm the presence of fuel in the oil.

#### ▲ Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. Fuel is present in the oil and is lowering the viscosity. The oil is no longer serviceable due to the presence of contaminants.

REPURI					FUEL
Series)		Nov2023	Ma/2024		X
IPLE INFORMATION	method	limit/base	current	history1	history2
e Number	Client Info		PCA0109574	LP0000978	
<b>.</b>	0" 11 (			0111 0000	

SAMPLE INFORI	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0109574	LP0000978	
Sample Date		Client Info		06 Mar 2024	01 Nov 2023	
Machine Age	hrs	Client Info		6015	5251	
Oil Age	hrs	Client Info		500	500	
Oil Changed		Client Info		Changed	Changed	
Sample Status				SEVERE	SEVERE	
CONTAMINAT	ION	method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG	NEG	
Glycol		WC Method	7 0.2	NEG	NEG	
WEAR METAL	e	method	limit/base	ourront		hiotory?
				current	history1	history2
Iron	ppm	ASTM D5185m	>100	34	31	
Chromium	ppm	ASTM D5185m	>20	<1	0	
Nickel	ppm	ASTM D5185m	>4	0	0	
Titanium	ppm	ASTM D5185m		0	0	
Silver	ppm	ASTM D5185m	>3	0	0	
Aluminum	ppm	ASTM D5185m	>20	2	<1	
Lead	ppm	ASTM D5185m	>40	1	3	
Copper	ppm	ASTM D5185m	>330	6	8	
Tin	ppm	ASTM D5185m	>15	0	0	
Vanadium	ppm	ASTM D5185m		0	0	
Cadmium	ppm	ASTM D5185m		0	0	
A D D I TILL CO						
ADDITIVES		method	limit/base	current	history1	history2
ADDITIVES Boron	ppm	method ASTM D5185m	limit/base	current 19	history1 6	history2
	ppm		limit/base			•
Boron		ASTM D5185m	limit/base	19	6	
Boron Barium	ppm	ASTM D5185m ASTM D5185m	limit/base	19 0	6	
Boron Barium Molybdenum	ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m	limit/base	19 0 38	6 0 47	
Boron Barium Molybdenum Manganese	ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	limit/base	19 0 38 0	6 0 47	
Boron Barium Molybdenum Manganese Magnesium	ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	limit/base	19 0 38 0 105	6 0 47 0 712	
Boron Barium Molybdenum Manganese Magnesium Calcium	ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	limit/base	19 0 38 0 105 1656	6 0 47 0 712 936	
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus	ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	limit/base	19 0 38 0 105 1656 697	6 0 47 0 712 936 840	
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc	ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	limit/base	19 0 38 0 105 1656 697 852	6 0 47 0 712 936 840 1051	
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur	ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	limit/base	19 0 38 0 105 1656 697 852 2760	6 0 47 0 712 936 840 1051 2533	
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m	limit/base	19 0 38 0 105 1656 697 852 2760	6 0 47 0 712 936 840 1051 2533 history1	history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon	ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m	limit/base	19 0 38 0 105 1656 697 852 2760 current	6 0 47 0 712 936 840 1051 2533 history1	history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium	ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m	limit/base >25	19 0 38 0 105 1656 697 852 2760 current 3	6 0 47 0 712 936 840 1051 2533 history1 3	history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m	limit/base >25 >20	19 0 38 0 105 1656 697 852 2760 current 3 3	6 0 47 0 712 936 840 1051 2533 history1 3 3	history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium Fuel	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m	limit/base >25 >20 >5	19 0 38 0 105 1656 697 852 2760 current 3 3 2 ▲ 16.6	6 0 47 0 712 936 840 1051 2533 history1 3 3 <1	history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium Fuel INFRA-RED	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m	limit/base >25 >20 >5 limit/base >3	19 0 38 0 105 1656 697 852 2760 current 3 3 2 ▲ 16.6 current	6 0 47 0 712 936 840 1051 2533 history1 3 3 <1 ▲ 15.9	history2 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium Fuel INFRA-RED Soot %	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m	limit/base >25 >20 >5 limit/base >3	19 0 38 0 105 1656 697 852 2760 current 3 3 2 ▲ 16.6 current 0.2	6 0 47 0 712 936 840 1051 2533 history1 3 3 <1 ▲ 15.9 history1 0.2	history2 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium Fuel INFRA-RED Soot % Nitration	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D7844 *ASTM D7624 *ASTM D7624	limit/base >25 >20 >5 limit/base >3 >20	19 0 38 0 105 1656 697 852 2760 current 3 3 2 ▲ 16.6 current 0.2 9.5	6 0 47 0 712 936 840 1051 2533 history1 3 3 <1 ▲ 15.9 history1 0.2 8.7	history2 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium Fuel INFRA-RED Soot % Nitration Sulfation	ppm	ASTM D5185m ASTM D78185m ASTM D78144 *ASTM D7624 *ASTM D7624 *ASTM D7415 method	limit/base >25 >20 >5 limit/base >3 >20 >30 limit/base	19 0 38 0 105 1656 697 852 2760 current 3 3 2 ▲ 16.6 current 0.2 9.5 21.7 current	6 0 47 0 712 936 840 1051 2533 history1 3 3 <1 ▲ 15.9 history1 0.2 8.7 21.6 history1	history2 history2 history2 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur  CONTAMINAN Silicon Sodium Potassium Fuel INFRA-RED Soot % Nitration Sulfation	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D7844 *ASTM D7624 *ASTM D7624	limit/base >25 >20 >5 limit/base >3 >20 >3 >20 >30	19 0 38 0 105 1656 697 852 2760	6 0 47 0 712 936 840 1051 2533 history1 3 3 <1 ▲ 15.9 history1 0.2 8.7 21.6	history2 history2



## **OIL ANALYSIS REPORT**







Laboratory Sample No.

: WearCheck USA - 501 Madison Ave., Cary, NC 27513

Lab Number : 06130809 Unique Number: 10950274

: PCA0109574

Received : 27 Mar 2024 **Tested** Diagnosed

: 01 Apr 2024 : 01 Apr 2024 - Wes Davis

TRESCA BROS SAND & GRAVEL INC 66 MAIN ST MILLIS, MA US 02054 Contact: FRAN ROSSI

Test Package: MOB 2 (Additional Tests: PercentFuel) Certificate L2367 To discuss this sample report, contact Customer Service at 1-800-237-1369.

frossi@trescaconcrete.com T: (508)376-2957

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: (508)376-4333