

OIL ANALYSIS REPORT

Sample Rating Trend NORMAL

Machine Id **834000**

Component

Transmission (Auto)

PETRO CANADA DuraDrive HD Synthetic 668 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the fluid.


Fluid Condition

The condition of the fluid is acceptable for the time in service.

008 (GAL)				Mar2024		
SAMPLE INFOR	RMATION	method	limit/base	current	history1	history2
Sample Number		Client Info		GFL0106803		
Sample Date		Client Info		21 Mar 2024		
Machine Age	hrs	Client Info		2389		
Oil Age	hrs	Client Info		600		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
CONTAMINA	TION	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR META	LS	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>160	97		
Chromium	ppm	ASTM D5185m	>5	<1		
Nickel	ppm	ASTM D5185m	>5	1		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m	>5	<1		
Aluminum	ppm	ASTM D5185m	>50	27		
Lead	ppm	ASTM D5185m	>50	8		
Copper	ppm	ASTM D5185m	>225	10		
Tin	ppm	ASTM D5185m	>10	3		
Vanadium	ppm	ASTM D5185m	>10	<1		
Cadmium	ppm	ASTM D5185m		<1		
	ррпп			<u> </u>		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		90		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		<1		
Manganese	ppm	ASTM D5185m		2		
Magnesium	ppm	ASTM D5185m		2		
Calcium	ppm	ASTM D5185m		81		
Phosphorus	ppm	ASTM D5185m		292		
Zinc	ppm	ASTM D5185m		5		
Sulfur	ppm	ASTM D5185m		2503		
CONTAMINAL	NTS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	19		
Sodium	ppm	ASTM D5185m		5		
Potassium	ppm	ASTM D5185m	>20	4		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE	NONE		
Sand/Dirt	scalar	*Visual	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML		
Emulsified Water	scalar	*Visual	>0.1	NEG		
Free Water	scalar	*Visual		NEG		
37:14) Rev: 1					Submitted By: A	





OIL ANALYSIS REPORT




Visc @ 40°C	history2
	history2
Outro	
Color no image no image	no image
Bottom no image no image	no image

GRAPHS









Certificate L2367

Laboratory Sample No.

Test Package : FLEET

Lab Number : 06131514

: GFL0106803 Unique Number : 10950979

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received **Tested**

Diagnosed : 28 Mar 2024 - Wes Davis

: 27 Mar 2024 : 28 Mar 2024 GFL Environmental - 856 - Houston South 8515 Highway 6 South

Houston, TX US 77083 Contact: Apolinar Zacarias

pzacariascano@gflenv.com T:

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: