




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**10605 FREIGHTLINER M2 106**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON SHP 15W40 (48 GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>GFL0103171</b>	GFL0103214	GFL0089298
Sample Date	Client Info	<b>27 Mar 2024</b>	14 Dec 2023	15 Sep 2023
Machine Age	hrs	<b>29136</b>	28619	27997
Oil Age	hrs	<b>517</b>	622	789
Oil Changed	Client Info	<b>Not Changed</b>	Changed	Changed
Sample Status		<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method >0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method	<b>NEG</b>	NEG	NEG

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >90	<b>2</b>	10	24
Chromium	ppm ASTM D5185m >20	<b>&lt;1</b>	<1	1
Nickel	ppm ASTM D5185m >2	<b>&lt;1</b>	0	1
Titanium	ppm ASTM D5185m >2	<b>0</b>	0	<1
Silver	ppm ASTM D5185m >2	<b>0</b>	0	0
Aluminum	ppm ASTM D5185m >20	<b>2</b>	2	6
Lead	ppm ASTM D5185m >40	<b>0</b>	0	1
Copper	ppm ASTM D5185m >330	<b>0</b>	1	3
Tin	ppm ASTM D5185m >15	<b>0</b>	<1	<1
Vanadium	ppm ASTM D5185m	<b>0</b>	0	<1
Cadmium	ppm ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	<b>5</b>	4	4
Barium	ppm ASTM D5185m 0	<b>0</b>	0	0
Molybdenum	ppm ASTM D5185m 60	<b>52</b>	56	60
Manganese	ppm ASTM D5185m 0	<b>0</b>	<1	<1
Magnesium	ppm ASTM D5185m 1010	<b>894</b>	940	957
Calcium	ppm ASTM D5185m 1070	<b>958</b>	1023	1126
Phosphorus	ppm ASTM D5185m 1150	<b>993</b>	965	1064
Zinc	ppm ASTM D5185m 1270	<b>1185</b>	1248	1276
Sulfur	ppm ASTM D5185m 2060	<b>3506</b>	2930	3062

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	<b>3</b>	3	5
Sodium	ppm ASTM D5185m	<b>0</b>	<1	2
Potassium	ppm ASTM D5185m >20	<b>1</b>	0	3

## INFRA-RED



method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >6	<b>0.1</b>	0.4	0.5
Nitration	Abs/cm *ASTM D7624 >20	<b>4.7</b>	5.4	5.7
Sulfation	Abs/.1mm *ASTM D7415 >30	<b>17.8</b>	18.1	18.2

## FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	<b>13.9</b>	13.1	13.3
Base Number (BN)	mg KOH/g ASTM D2896 9.8	<b>8.8</b>	8.8	8.8







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	13.9	13.6

## GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
 Sample No. : GFL0103171  
 Lab Number : 06133025  
 Unique Number : 10952490  
 Test Package : FLEET

Received : 29 Mar 2024  
 Tested : 31 Mar 2024  
 Diagnosed : 31 Mar 2024 - Wes Davis

GFL Environmental - 001 - Raleigh(CNG)  
 3741 Conquest Drive  
 Garner, NC  
 US 27529

Contact: Craig Johnson  
 craig.johnson@gflenv.com

T: (919)662-7100  
 F: (919)662-7130

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)