




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**10100**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 15W40 (7 GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>GFL0115728</b>	GFL0109868	GFL0083199
Sample Date	Client Info	<b>28 Mar 2024</b>	11 Jan 2024	20 Jun 2023
Machine Age	hrs	<b>1</b>	11987	11226
Oil Age	hrs	<b>226</b>	182	558
Oil Changed	Client Info	<b>Not Chngd</b>	Not Chngd	Changed
Sample Status		<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method >0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method	<b>NEG</b>	NEG	NEG

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >90	<b>54</b>	35	91
Chromium	ppm ASTM D5185m >20	<b>1</b>	1	4
Nickel	ppm ASTM D5185m >2	<b>2</b>	<1	2
Titanium	ppm ASTM D5185m >2	<b>0</b>	0	<1
Silver	ppm ASTM D5185m >2	<b>0</b>	0	0
Aluminum	ppm ASTM D5185m >20	<b>7</b>	3	11
Lead	ppm ASTM D5185m >40	<b>&lt;1</b>	0	3
Copper	ppm ASTM D5185m >330	<b>0</b>	1	5
Tin	ppm ASTM D5185m >15	<b>&lt;1</b>	0	<1
Vanadium	ppm ASTM D5185m	<b>0</b>	0	<1
Cadmium	ppm ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	<b>12</b>	3	16
Barium	ppm ASTM D5185m 0	<b>0</b>	3	0
Molybdenum	ppm ASTM D5185m 60	<b>45</b>	56	62
Manganese	ppm ASTM D5185m 0	<b>&lt;1</b>	0	1
Magnesium	ppm ASTM D5185m 1010	<b>688</b>	842	715
Calcium	ppm ASTM D5185m 1070	<b>1140</b>	968	1103
Phosphorus	ppm ASTM D5185m 1150	<b>916</b>	904	899
Zinc	ppm ASTM D5185m 1270	<b>1099</b>	1109	1144
Sulfur	ppm ASTM D5185m 2060	<b>3039</b>	3032	3224

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	<b>9</b>	8	25
Sodium	ppm ASTM D5185m	<b>7</b>	3	21
Potassium	ppm ASTM D5185m >20	<b>2</b>	2	4

## INFRA-RED



method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >6	<b>2.2</b>	1.7	2.9
Nitration	Abs/cm *ASTM D7624 >20	<b>9.7</b>	8.1	12.5
Sulfation	Abs/.1mm *ASTM D7415 >30	<b>20.8</b>	20.4	25.7

## FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	<b>14.2</b>	13.5	18.5
Base Number (BN)	mg KOH/g ASTM D2896 9.8	<b>8.5</b>	8.5	6.8







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.0</b>	13.5	13.41

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0115728 **Received** : 29 Mar 2024  
**Lab Number** : **06133118** **Tested** : 31 Mar 2024  
**Unique Number** : 10952583 **Diagnosed** : 31 Mar 2024 - Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 010 - Stockbridge**  
 1280 Rum Creek Parkway  
 Stockbridge, GA  
 US 30281  
 Contact: JOSHUA TINKER  
 joshuatinker@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)