OIL DIAGNOSTICS

OIL ANALYSIS REPORT

Sample Rating Trend



ISO

Area
GRIND ROOM [98738639]
Machine Id
KR-GR-003073 - DUMPER 7A - SOUTH (S/N GRIND A - 11513014)
Component
Hydraulic System
Fluid
AW HYDRAULIC OIL ISO 68 (10 GAL)

DIAGNOSIS

Recommendation

We recommend you service the filters on this component if applicable. Resample at the next service interval to monitor. (Customer Sample Comment: 98738639)

Wear

All component wear rates are normal.

Contamination

There is a high amount of silt (particulates < 14 microns in size) present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number		Client Info		**PCA0113110**	PCA0115888	PCA0106508
Sample Date		Client Info		**14 Mar 2024**	13 Mar 2024	20 Dec 2023
Machine Age	hrs	Client Info		**0**	0	0
Oil Age	hrs	Client Info		**0**	0	0
Oil Changed		Client Info		**N/A**	N/A	Not Changd
Sample Status				**ABNORMAL**	NORMAL	NORMAL

CONTAMINATION		method	limit/base	current	history1	history2
Water		WC Method	>0.05	**NEG**	NEG	NEG

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	**0**	0	0
Chromium	ppm	ASTM D5185m	>20	**<1**	<1	0
Nickel	ppm	ASTM D5185m	>20	**0**	0	0
Titanium	ppm	ASTM D5185m		**<1**	<1	0
Silver	ppm	ASTM D5185m		**0**	0	0
Aluminum	ppm	ASTM D5185m	>20	**3**	3	0
Lead	ppm	ASTM D5185m	>20	**<1**	<1	0
Copper	ppm	ASTM D5185m	>20	**<1**	<1	0
Tin	ppm	ASTM D5185m	>20	**<1**	<1	0
Vanadium	ppm	ASTM D5185m		**<1**	<1	0
Cadmium	ppm	ASTM D5185m		**<1**	<1	0

ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	5	**0**	0	0
Barium	ppm	ASTM D5185m	5	**<1**	0	0
Molybdenum	ppm	ASTM D5185m	5	**0**	0	0
Manganese	ppm	ASTM D5185m		**0**	0	<1
Magnesium	ppm	ASTM D5185m	25	**<1**	<1	0
Calcium	ppm	ASTM D5185m	200	**3**	4	0
Phosphorus	ppm	ASTM D5185m	300	**366**	354	286
Zinc	ppm	ASTM D5185m	370	**5**	5	0
Sulfur	ppm	ASTM D5185m	2500	**433**	409	194

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	**2**	2	1
Sodium	ppm	ASTM D5185m		**0**	0	3
Potassium	ppm	ASTM D5185m	>20	**<1**	1	1

FLUID CLEANLINESS		method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	▲ **20947**	9501	3170
Particles >6µm		ASTM D7647	>2500	▲ **6026**	1243	214
Particles >14µm		ASTM D7647	>640	**501**	64	20
Particles >21µm		ASTM D7647	>160	**116**	20	4
Particles >38µm		ASTM D7647	>40	**6**	2	0
Particles >71µm		ASTM D7647	>10	**0**	0	0
Oil Cleanliness		ISO 4406 (c)	>20/18/16	▲ **22/20/16**	20/17/13	19/15/11

FLUID DEGRADATION		method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.57	**0.27**	0.27	0.25

OIL ANALYSIS REPORT

OIL DIAGNOSTICS

Particle Trend



Particle Trend



Acid Number



Viscosity @ 40°C



VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	**NONE**	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	**NONE**	NONE	NONE
Precipitate	scalar	*Visual	NONE	**NONE**	NONE	NONE
Silt	scalar	*Visual	NONE	**NONE**	NONE	NONE
Debris	scalar	*Visual	NONE	**NONE**	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	**NONE**	NONE	NONE
Appearance	scalar	*Visual	NORML	**NORML**	NORML	NORML
Odor	scalar	*Visual	NORML	**NORML**	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	**NEG**	NEG	NEG
Free Water	scalar	*Visual		**NEG**	NEG	NEG

FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	68	**67.1**	68.3	67.0

SAMPLE IMAGES	method	limit/base	current	history1	history2
Color					
Bottom					

GRAPHS

Ferrous Alloys



Non-ferrous Metals



Viscosity @ 40°C



Particle Count



Acid Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0113110
Lab Number : 06133237
Unique Number : 10952702
Test Package : IND 2

Received : 29 Mar 2024
Tested : 01 Apr 2024
Diagnosed : 03 Apr 2024 - Don Baldridge

KraftHeinz - Kirksville - Plant 8333 PCA
2504 INDUSTRIAL DR
KIRKSVILLE, MO
US 63501
Contact: Wilberto Pacheco Garcia
Wilberto.PachecoGarcia@kraftheinz.com
T:
F: (660)627-5887

To discuss this sample report, contact Customer Service at 1-800-237-1369.
** - Denotes test methods that are outside of the ISO 17025 scope of accreditation.*
Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)