

Area

**MIX ROOM A [98763414]**

Machine Id


**KR-GR-003108 - W DUMPER 14A (S/N MIX A - 11513051)**

Component

**Hydraulic System**

Fluid

**AW HYDRAULIC OIL ISO 68 (--- GAL)**



## DIAGNOSIS

### Recommendation

We recommend you service the filters on this component if applicable. Resample at the next service interval to monitor. ( Customer Sample Comment: 98763414 )

### Wear

All component wear rates are normal.

### Contamination

There is a high amount of silt (particulates < 14 microns in size) present in the oil.

### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>PCA0116072</b>	PCA0088775	PCA0111171
Sample Date	Client Info	<b>14 Mar 2024</b>	11 Jan 2024	28 Dec 2023
Machine Age	hrs	<b>0</b>	0	0
Oil Age	hrs	<b>0</b>	0	0
Oil Changed	Client Info	<b>N/A</b>	N/A	N/A
Sample Status		<b>ABNORMAL</b>	NORMAL	ABNORMAL

## CONTAMINATION

method	limit/base	current	history1	history2
Water	WC Method >0.05	<b>NEG</b>	NEG	NEG

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >20	<b>8</b>	4	6
Chromium	ppm ASTM D5185m >20	<b>3</b>	1	2
Nickel	ppm ASTM D5185m >20	<b>&lt;1</b>	0	0
Titanium	ppm ASTM D5185m	<b>&lt;1</b>	0	0
Silver	ppm ASTM D5185m	<b>0</b>	0	0
Aluminum	ppm ASTM D5185m >20	<b>3</b>	2	1
Lead	ppm ASTM D5185m >20	<b>&lt;1</b>	0	0
Copper	ppm ASTM D5185m >20	<b>&lt;1</b>	0	0
Tin	ppm ASTM D5185m >20	<b>&lt;1</b>	0	0
Vanadium	ppm ASTM D5185m	<b>&lt;1</b>	0	0
Cadmium	ppm ASTM D5185m	<b>&lt;1</b>	0	0

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 5	<b>0</b>	0	0
Barium	ppm ASTM D5185m 5	<b>0</b>	0	0
Molybdenum	ppm ASTM D5185m 5	<b>0</b>	0	0
Manganese	ppm ASTM D5185m	<b>&lt;1</b>	0	<1
Magnesium	ppm ASTM D5185m 25	<b>0</b>	0	0
Calcium	ppm ASTM D5185m 200	<b>3</b>	2	0
Phosphorus	ppm ASTM D5185m 300	<b>363</b>	384	321
Zinc	ppm ASTM D5185m 370	<b>2</b>	0	0
Sulfur	ppm ASTM D5185m 2500	<b>434</b>	419	237

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >15	<b>1</b>	0	1
Sodium	ppm ASTM D5185m	<b>0</b>	0	4
Potassium	ppm ASTM D5185m >20	<b>1</b>	<1	2





## FLUID CLEANLINESS

method	limit/base	current	history1	history2
Particles >4µm	ASTM D7647 >10000	<b>▲ 217667</b>	---	▲ 179053
Particles >6µm	ASTM D7647 >2500	<b>▲ 63121</b>	---	▲ 31199
Particles >14µm	ASTM D7647 >640	<b>402</b>	---	227
Particles >21µm	ASTM D7647 >160	<b>47</b>	---	40
Particles >38µm	ASTM D7647 >40	<b>1</b>	---	1
Particles >71µm	ASTM D7647 >10	<b>0</b>	---	0
Oil Cleanliness	ISO 4406 (c) >20/18/16	<b>▲ 25/23/16</b>	---	▲ 25/22/15

## FLUID DEGRADATION

method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g ASTM D8045 0.57	<b>0.08</b>	---	0.08


# OIL ANALYSIS REPORT








VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	68	66.3	66.7

SAMPLE IMAGES	method	limit/base	current	history1	history2
---------------	--------	------------	---------	----------	----------



## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0116072  
**Lab Number** : 06133244  
**Unique Number** : 10952709  
**Test Package** : IND 2

**KraftHeinz - Kirksville - Plant 8333 PCA**  
 2504 INDUSTRIAL DR  
 KIRKSVILLE, MO  
 US 63501  
 Contact: WALLACE WARD  
 wallace.ward@kraftheinzcompany.com  
 T: (660)627-1031  
 F: (660)627-5887

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)