

OIL ANALYSIS REPORT

Area **STUFF ROOM C [98826629]** Machine Id **KR-GR-001589 - MARLEN (S/N STUFF C - 11513126)**

Hydraulic System

AW HYDRAULIC OIL ISO 68 (60 GAL)

DIAGNOSIS

Recommendation

We recommend you service the filters on this component if applicable. Resample at the next service interval to monitor. We were unable to perform a particle count due to a high concentration of particles present in this sample. (Customer Sample Comment: 98826629)

Wear


All component wear rates are normal.

Contamination

Moderate concentration of visible dirt/debris present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is acceptable for the time in service.




SAMPLE INFOR	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0115880	PCA0111179	PCA009176
Sample Date		Client Info		14 Mar 2024	20 Dec 2023	05 Sep 2023
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	Not Changd	N/A
Sample Status				ABNORMAL	NORMAL	ABNORMAL
CONTAMINAT	ION	method	limit/base	current	history1	history2
Water		WC Method	>0.05	NEG	NEG	NEG
WEAR METAL	S	method	limit/base	current	history1	history2
ron	ppm	ASTM D5185m	>20	0	0	<1
Chromium	ppm	ASTM D5185m	>20	<1	0	0
Nickel	ppm	ASTM D5185m	>20	0	0	0
Titanium	ppm	ASTM D5185m		<1	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>20	3	0	<1
_ead	ppm	ASTM D5185m	>20	<1	0	0
Copper	ppm	ASTM D5185m	>20	<1	0	<1
Tin	ppm	ASTM D5185m	>20	<1	0	0
Vanadium	ppm	ASTM D5185m		<1	0	0
Cadmium	ppm	ASTM D5185m		<1	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	5	0	0	0
Barium	ppm	ASTM D5185m	5	0	0	0
Molybdenum	ppm	ASTM D5185m	5	0	0	0
Vanganese	ppm	ASTM D5185m		0	<1	<1
Magnesium	ppm	ASTM D5185m	25	<1	0	<1
Calcium	ppm	ASTM D5185m	200	3	0	2
Phosphorus	ppm	ASTM D5185m	300	497	418	447
Zinc	ppm	ASTM D5185m	370	3	0	5
Sulfur	ppm	ASTM D5185m	2500	499	282	579
CONTAMINAN	ITS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	3	1	2
Sodium	ppm	ASTM D5185m		0	3	0
Potassium	ppm	ASTM D5185m	>20	1	1	0
FLUID CLEAN	LINESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000		3248	
Particles >6µm		ASTM D7647	>2500		395	
Particles >14µm		ASTM D7647	>640		38	
Particles >21µm		ASTM D7647	>160		12	
Dortiolog , 20um		ASTM D7647	>40		1	
Particles >38µm			10		0	
Particles >36µm Particles >71µm		ASTM D7647	>10		0	
		ASTM D7647 ISO 4406 (c)	>10		19/16/12	
Particles >71µm		ISO 4406 (c)				


Report Id: KRAKIR [WUSCAR] 06133250 (Generated: 04/03/2024 15:28:36) Rev: 1

Submitted By: Wilberto Pacheco Garcia




OIL ANALYSIS REPORT





VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	A MODER	NONE	🔺 MODER
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPE	RTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	68	66.0	66.4	66.1
SAMPLE IMAG	iES	method	limit/base	current	history1	history2
Color						
Bottom						



Submitted By: Wilberto Pacheco Garcia