

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Area FRONT LOAD Machine Id FEL240965

Component Transmission

Fluid {not provided} (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the fluid.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the fluid is suitable for further service.

SAMPLE INFORM	/ ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0109920		
Sample Date		Client Info		21 Mar 2024		
Machine Age	hrs	Client Info		993		
Oil Age	hrs	Client Info		993		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
CONTAMINATI	ON	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS	S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>320	68		
Chromium	ppm	ASTM D5185m	>5	0		
Nickel	ppm	ASTM D5185m	>5	<1		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>50	14		
Lead	ppm	ASTM D5185m	>65	2		
Copper	ppm	ASTM D5185m	>95	13		
Tin	ppm	ASTM D5185m	>6	1		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		60		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		<1		
Manganese	ppm	ASTM D5185m		1		
Magnesium	ppm	ASTM D5185m		0		
Calcium	ppm	ASTM D5185m		161		
Phosphorus	ppm	ASTM D5185m		209		
Zinc	ppm	ASTM D5185m		12		
Sulfur	ppm	ASTM D5185m		2021		
CONTAMINAN	TS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>65	15		
Sodium	ppm	ASTM D5185m		5		
Potassium	ppm	ASTM D5185m	>20	3		
FLUID DEGRAD	ATION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		1.11		



OIL ANALYSIS REPORT

VISUAL



	White Metal	scalar	*Visual	NONE	NONE						
	Yellow Metal	scalar	*Visual	NONE	NONE						
	Precipitate	scalar	*Visual	NONE	NONE						
	Silt	scalar	*Visual	NONE	LIGHT						
	Debris	scalar	*Visual	NONE	NONE						
	Sand/Dirt	scalar	*Visual	NONE	NONE						
21/24	Appearance	scalar	*Visual	NORML	NORML						
Mar	Odor	scalar	*Visual	NORML	NORML						
	Emulsified Water	scalar	*Visual	>0.1	NEG						
1	Free Water	scalar	*Visual		NEG						
	FLUID PROPE	RTIES	method	limit/base	current	history1	history2				
	Visc @ 40°C	cSt	ASTM D445		32.5						
		EQ	method	limit/base	current	history1	history?				
			memou	iiiiii/base	current	HISTOLA	Thistory 2				
Mai21/24	Color				no image	no image	no image				
	Bottom				no image	no image	no image				
	GRAPHS										
	Iron (ppm)			10	Lead (ppm)						
	= 400 - Abnormal				Severe						
	Ē. 200			dd g	Abnormal						
				5	0		4				
	ar21/2			ar21/2	ar21/2		ar21/2				
	≥ Aluminum (nnm)			≥	≥ Chromium (nr	um)	M				
	¹⁰⁰ Severe				⁵ TC						
	E 50 Abnormal			E ¹	0 - Severe						
					5 - Q						
	74			/24	74		/24				
	Mar21			Mar21	Mar21		Mar21				
	Copper (ppm)				Silicon (ppm)						
	200 Severe			15	Severe						
	톱 100 - Abnormal			E C	Abnormal						
	0			`	0						
	r21/24			21/24	r21/24		(21/24				
	Ma			Ma	Ma		Ma				
	Viscosity @ 40°C			(B/H0)	Acid Number						
	Co 100 Abnormal			- <u>E</u> 1	.0						
	황 50			0 mp	.5						
	25			24 + keid N			24 +				
	/lar21/			Mar21/	Mar21/		//ar21/				
Laboratory Sample No. Lab Number Unique Number Test Package To discuss this sample report * - Denotes test methods that	: WearCheck USA - 501 : PCA0109920 : 06133546 : 10953011 : MOB 2 , contact Customer Servi are outside of the ISO 12	Madison Ave., Cary, NC 27513 Received : 29 Mar 2024 Tested : 01 Apr 2024 Diagnosed : 03 Apr 2024 - Don Baldridge the at 1-800-237-1369. 1025 scope of accreditation.			UMM - Shop 401 - Norton 186 South Washington Street Norton, MA US 02766 Contact: P Cohen pcohen@win-waste.com T:						
Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012) F:											