




OIL ANALYSIS REPORT

Sample Rating Trend



GLYCOL



Machine Id
12036
 Component
Diesel Engine
 Fluid

PETRO CANADA DURON SHP 15W40 (32 QTS)

DIAGNOSIS

Recommendation

We advise that you check for the source of the coolant leak. Check for low coolant level. The oil change at the time of sampling has been noted. We recommend an early resample to monitor this condition.

Wear

All component wear rates are normal.

Contamination

Sodium and/or potassium levels are high.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	GFL0068835	GFL0068878	GFL0068859
Sample Date	Client Info	29 Mar 2024	08 Feb 2024	13 Jan 2024
Machine Age	hrs	14332	13968	13843
Oil Age	hrs	489	125	538
Oil Changed	Client Info	Changed	Not Changd	Changed
Sample Status		ABNORMAL	NORMAL	NORMAL

CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >3.0	<1.0	<1.0	<1.0
Water	WC Method >0.2	NEG	NEG	NEG

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >75	14	5	11
Chromium	ppm ASTM D5185m >5	<1	<1	<1
Nickel	ppm ASTM D5185m >4	0	0	0
Titanium	ppm ASTM D5185m >2	0	<1	0
Silver	ppm ASTM D5185m >2	0	0	0
Aluminum	ppm ASTM D5185m >15	2	3	3
Lead	ppm ASTM D5185m >25	0	0	0
Copper	ppm ASTM D5185m >100	0	0	1
Tin	ppm ASTM D5185m >4	0	0	0
Vanadium	ppm ASTM D5185m	0	0	<1
Cadmium	ppm ASTM D5185m	0	0	0

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	6	6	1
Barium	ppm ASTM D5185m 0	0	0	0
Molybdenum	ppm ASTM D5185m 60	62	55	55
Manganese	ppm ASTM D5185m 0	<1	<1	0
Magnesium	ppm ASTM D5185m 1010	867	860	859
Calcium	ppm ASTM D5185m 1070	951	932	913
Phosphorus	ppm ASTM D5185m 1150	967	978	953
Zinc	ppm ASTM D5185m 1270	1144	1129	1151
Sulfur	ppm ASTM D5185m 2060	3189	2808	2868

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	6	7	5
Sodium	ppm ASTM D5185m	▲ 187	64	124
Potassium	ppm ASTM D5185m >20	3	0	4
Glycol	% *ASTM D2982	NEG	NEG	0.0

INFRA-RED

method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >6	0.6	0.2	0.4
Nitration	Abs/cm *ASTM D7624 >20	9.1	5.8	8.3
Sulfation	Abs/.1mm *ASTM D7415 >30	19.0	17.6	18.3


FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	15.3	13.1	14.4
Base Number (BN)	mg KOH/g ASTM D2896 9.8	7.4	8.3	7.9




OIL ANALYSIS REPORT


FT-IR (Direct Trend)




Glycol Contamination



Viscosity @ 100°C



Glycol Contamination




VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG


FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	12.9	13.1

GRAPHS


Ferrous Alloys





Non-ferrous Metals



Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513

Sample No. : GFL0068835

Lab Number : 06136034

Unique Number : 10955499

Test Package : FLEET (Additional Tests: Glycol)

Received : 02 Apr 2024

Tested : 04 Apr 2024

Diagnosed : 04 Apr 2024 - Jonathan Hester

GFL Environmental - 073 - Warner Robins - Transwaste

155 Story Road

Warner Robins, GA

US 31093

Contact: JOSH MALONEY

jmaloney@gflenv.com

T:

F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)