

OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id **732006** Component **Transmission (Auto)**

Fluid PETRO CANADA DuraDrive HD Synthetic 668 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the fluid.


Fluid Condition

The condition of the fluid is acceptable for the time in service.

			00112023	Martory		
SAMPLE INFORM	IATION	method				history2
Sample Number		Client Info		GFL0106922	GFL0084676	
Sample Date		Client Info		28 Mar 2024	08 Jun 2023	
Machine Age	hrs	Client Info		7286	55080	
Oil Age	hrs	Client Info		1200	0	
Oil Changed		Client Info		Changed	Changed	
Sample Status				NORMAL	ABNORMAL	
CONTAMINATI		and the set	1			history O
	ON	method	limit/base	current	history1	history2
Water			>0.1	NEG	NEG	
WEAR METALS	5	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>160	60	36	
Chromium	ppm	ASTM D5185m	>5	<1	0	
Nickel	ppm	ASTM D5185m	>5	0	0	
Titanium	ppm	ASTM D5185m		0	0	
Silver	ppm	ASTM D5185m	>5	0	0	
Aluminum	ppm	ASTM D5185m	>50	17	6	
Lead	ppm	ASTM D5185m	>50	3	2	
Copper	ppm	ASTM D5185m	>225	11	6	
Tin	ppm	ASTM D5185m	>10	2	<1	
Vanadium	ppm	ASTM D5185m		<1	0	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		60	68	
Barium	ppm	ASTM D5185m		0	2	
Molybdenum	ppm	ASTM D5185m		<1	<1	
Manganese	ppm	ASTM D5185m		<1	<1	
Magnesium	ppm	ASTM D5185m		0	2	
Calcium	ppm	ASTM D5185m		108	120	
Phosphorus	ppm	ASTM D5185m		203	220	
Zinc	ppm	ASTM D5185m		0	10	
Sulfur	ppm	ASTM D5185m		1741	1720	
CONTAMINAN	ΓS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	3	3	
Sodium	ppm	ASTM D5185m		8	1	
Potassium	ppm	ASTM D5185m		3	3	
VISUAL		method	limit/base	current	history1	history2
White Metal						
write weta	scalar	*Visual	NONE	NONE	🔺 MODER	
	scalar scalar	*Visual *Visual	NONE NONE	NONE NONE	MODER NONE	
Yellow Metal						
Yellow Metal Precipitate	scalar	*Visual	NONE	NONE	NONE	
Yellow Metal Precipitate Silt	scalar scalar	*Visual *Visual	NONE NONE	NONE NONE	NONE NONE	
Yellow Metal Precipitate Silt Debris	scalar scalar scalar	*Visual *Visual *Visual	NONE NONE NONE	NONE NONE NONE	NONE NONE NONE	
Yellow Metal Precipitate Silt Debris Sand/Dirt	scalar scalar scalar scalar	*Visual *Visual *Visual *Visual	NONE NONE NONE NONE	NONE NONE NONE NONE	NONE NONE NONE NONE	
Yellow Metal Precipitate Silt Debris Sand/Dirt Appearance Odor	scalar scalar scalar scalar scalar	*Visual *Visual *Visual *Visual *Visual	NONE NONE NONE NONE	NONE NONE NONE NONE NONE	NONE NONE NONE NONE	
Yellow Metal Precipitate Silt Debris Sand/Dirt Appearance	scalar scalar scalar scalar scalar scalar	*Visual *Visual *Visual *Visual *Visual *Visual	NONE NONE NONE NONE NONE	NONE NONE NONE NONE NORE	NONE NONE NONE NONE NORML	
Yellow Metal Precipitate Silt Debris Sand/Dirt Appearance Odor	scalar scalar scalar scalar scalar scalar	*Visual *Visual *Visual *Visual *Visual *Visual	NONE NONE NONE NONE NORML NORML	NONE NONE NONE NONE NORML NORML	NONE NONE NONE NONE NORML NORML	



OIL ANALYSIS REPORT



	FLUID PROPE Visc @ 40°C	cSt ASTM D	od limit/base	current 31.9	history1 32.9	history
	SAMPLE IMAG			current	history1	history
			[,
	Color			no image	no image	no image
Mar28/24						
	Bottom			no image	no image	no image
	GRAPHS Ferrous Alloys					
		~	and the second se			
	50 - Seessee chromium					
	40 -					
	<u>특</u> 30 -					
	20-					
	10-					
	0					
	Jun8/23		Mar28/24			
	Non-ferrous Meta	S	2			
	11 10 copper		and the second se			
	9 - Bessesses lead					
	7-					
	e 6 5					
	3-					
	2					
	0		- 54			
	//23					
	Jun8/23		Mar28/24			
	Viscosity @ 40°C		Mar28,			
	Viscosity @ 40°C		Mar28,			
	Viscosity @ 40°C		Mar28			
	Viscosity @ 40°C		Ma28			
	Viscosity @ 40°C		Ma28			
	Viscosity @ 40°C		Wa28			
	Viscosity @ 40°C		Wa28			
	Viscosity @ 40°C					
	Viscosity @ 40°C		Ma28/24			
Laboratory	Viscosity @ 40°C	1 Madison Ave	Ma28/24	GEL En	vironmental - 856	- Houston Sr
Laboratory Sample No.	Viscosity @ 40°C	Received	Cary, NC 27513 : 02 Apr 2024	GFL Env	vironmental - 856 8515 Hi	ghway 6 Sc
	Viscosity @ 40°C					

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)