


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
333131
 Component
Diesel Engine
 Fluid
PETRO CANADA DURON SHP 10W30 (--- QTS)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

Wear

Metal levels are typical for a new component breaking in.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			PCA0119406	PCA0097310	PCA0083817
Sample Date	Client Info			28 Feb 2024	09 Jan 2024	31 May 2023
Machine Age	mls	Client Info		38445	34339	17365
Oil Age	mls	Client Info		21080	16974	17365
Oil Changed	Client Info			Changed	Not Changd	Changed
Sample Status				NORMAL	NORMAL	NORMAL

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>5		<1.0	<1.0	0.4
Water	WC Method	>0.2		NEG	NEG	NEG
Glycol	WC Method			NEG	NEG	NEG

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	25	24	56
Chromium	ppm	ASTM D5185m	>20	<1	1	3
Nickel	ppm	ASTM D5185m	>4	0	<1	2
Titanium	ppm	ASTM D5185m		7	2	6
Silver	ppm	ASTM D5185m	>3	0	0	1
Aluminum	ppm	ASTM D5185m	>20	13	13	14
Lead	ppm	ASTM D5185m	>40	0	0	5
Copper	ppm	ASTM D5185m	>330	12	13	36
Tin	ppm	ASTM D5185m	>15	1	2	5
Vanadium	ppm	ASTM D5185m		<1	<1	1
Cadmium	ppm	ASTM D5185m		0	0	2




ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	2	12	6	43
Barium	ppm	ASTM D5185m	0	0	0	19
Molybdenum	ppm	ASTM D5185m	50	55	62	40
Manganese	ppm	ASTM D5185m	0	1	1	9
Magnesium	ppm	ASTM D5185m	950	928	942	414
Calcium	ppm	ASTM D5185m	1050	1256	1155	1339
Phosphorus	ppm	ASTM D5185m	995	1076	1050	631
Zinc	ppm	ASTM D5185m	1180	1290	1232	778
Sulfur	ppm	ASTM D5185m	2600	3853	3102	2299

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	4	6	10
Sodium	ppm	ASTM D5185m		3	3	7
Potassium	ppm	ASTM D5185m	>20	20	20	25

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	0.3	0.3	0.4
Nitration	Abs/cm	*ASTM D7624	>20	8.9	8.4	10.3
Sulfation	Abs/.1mm	*ASTM D7415	>30	18.9	18.7	23.2

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	15.9	15.4	21.7
Base Number (BN)	mg KOH/g	ASTM D2896		7.9	8.3	9.9









OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	12.00	10.5	10.6	9.2

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0119406 **Received** : 04 Apr 2024
Lab Number : 06138320 **Tested** : 05 Apr 2024
Unique Number : 10963128 **Diagnosed** : 05 Apr 2024 - Wes Davis
Test Package : MOB 1 (Additional Tests: TBN)

MILLER TRUCK LEASING #123
 66 KELLER AVENUE
 LANCASTER, PA
 US 17601
 Contact: RON ROBERTS
 roberts@millertransgroup.com
 T: (717)945-6205
 F: (717)945-5818

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)