


# OIL ANALYSIS REPORT

**Sample Rating Trend**

**NORMAL**


Area  
**(50955Z) Walgreens - Tractor**  
 Machine Id  
**[Walgreens - Tractor] 136A63288**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 10W30 (11 GAL)**

**DIAGNOSIS**
**Recommendation**

Resample at the next service interval to monitor.

**Wear**

All component wear rates are normal.

**Contamination**

There is no indication of any contamination in the oil.

**Fluid Condition**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			<b>PCA0117292</b>	PCA0094337	---
Sample Date	Client Info			<b>01 Apr 2024</b>	31 Oct 2023	---
Machine Age	mls	Client Info		<b>200231</b>	748551	---
Oil Age	mls	Client Info		<b>0</b>	0	---
Oil Changed	Client Info			<b>N/A</b>	N/A	---
Sample Status				<b>NORMAL</b>	NORMAL	---

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>5		<b>&lt;1.0</b>	<1.0	---
Water	WC Method	>0.2		<b>NEG</b>	NEG	---
Glycol	WC Method			<b>NEG</b>	NEG	---

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>80	<b>28</b>	32	---
Chromium	ppm	ASTM D5185m	>5	<b>3</b>	3	---
Nickel	ppm	ASTM D5185m	>2	<b>&lt;1</b>	<1	---
Titanium	ppm	ASTM D5185m		<b>&lt;1</b>	0	---
Silver	ppm	ASTM D5185m	>3	<b>&lt;1</b>	<1	---
Aluminum	ppm	ASTM D5185m	>30	<b>12</b>	13	---
Lead	ppm	ASTM D5185m	>30	<b>&lt;1</b>	0	---
Copper	ppm	ASTM D5185m	>150	<b>34</b>	38	---
Tin	ppm	ASTM D5185m	>5	<b>&lt;1</b>	<1	---
Vanadium	ppm	ASTM D5185m		<b>&lt;1</b>	0	---
Cadmium	ppm	ASTM D5185m		<b>&lt;1</b>	<1	---




ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	2	<b>2</b>	0	---
Barium	ppm	ASTM D5185m	0	<b>0</b>	4	---
Molybdenum	ppm	ASTM D5185m	50	<b>64</b>	62	---
Manganese	ppm	ASTM D5185m	0	<b>1</b>	<1	---
Magnesium	ppm	ASTM D5185m	950	<b>962</b>	907	---
Calcium	ppm	ASTM D5185m	1050	<b>1146</b>	1097	---
Phosphorus	ppm	ASTM D5185m	995	<b>974</b>	809	---
Zinc	ppm	ASTM D5185m	1180	<b>1224</b>	1184	---
Sulfur	ppm	ASTM D5185m	2600	<b>2393</b>	2440	---

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	<b>8</b>	8	---
Sodium	ppm	ASTM D5185m		<b>1</b>	0	---
Potassium	ppm	ASTM D5185m	>20	<b>23</b>	34	---

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	<b>0.7</b>	0.8	---
Nitration	Abs/cm	*ASTM D7624	>20	<b>9.8</b>	10.4	---
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>22.0</b>	23.1	---

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>19.2</b>	20.3	---
Base Number (BN)	mg KOH/g	ASTM D2896		<b>5.7</b>	5.5	---





# OIL ANALYSIS REPORT



PARAMETER	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	12.00	11.4	11.8

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0117292      **Received** : 05 Apr 2024  
**Lab Number** : **06140527**      **Tested** : 08 Apr 2024  
**Unique Number** : 10965335      **Diagnosed** : 08 Apr 2024 - Wes Davis  
**Test Package** : FLEET

**Transervice - Shop 1363 - Berkeley-Orlando**  
 2455 Premier Row  
 Orlando, FL  
 US 32809  
 Contact: James Bennett  
 jbennett@transervice.com  
 T: (407)856-8590  
 F: (407)856-2269

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)