




# OIL ANALYSIS REPORT



Machine Id  
**413010**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

### Sample Rating Trend



**NORMAL**



### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.

#### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

### SAMPLE INFORMATION

|               | method      | limit/base  | current            | history1    | history2    |
|---------------|-------------|-------------|--------------------|-------------|-------------|
| Sample Number | Client Info |             | <b>GFL0104441</b>  | GFL0104328  | GFL0110031  |
| Sample Date   | Client Info |             | <b>02 Apr 2024</b> | 04 Mar 2024 | 06 Feb 2024 |
| Machine Age   | hrs         | Client Info | <b>2846</b>        | 80          | 77          |
| Oil Age       | hrs         | Client Info | <b>600</b>         | 600         | 600         |
| Oil Changed   | Client Info |             | <b>Changed</b>     | Changed     | Changed     |
| Sample Status |             |             | <b>NORMAL</b>      | NORMAL      | NORMAL      |

### CONTAMINATION

|        | method    | limit/base | current        | history1 | history2 |
|--------|-----------|------------|----------------|----------|----------|
| Fuel   | WC Method | >3.0       | <b>&lt;1.0</b> | <1.0     | <1.0     |
| Water  | WC Method | >0.2       | <b>NEG</b>     | NEG      | NEG      |
| Glycol | WC Method |            | <b>NEG</b>     | NEG      | NEG      |

### WEAR METALS

|          | method | limit/base       | current      | history1 | history2 |
|----------|--------|------------------|--------------|----------|----------|
| Iron     | ppm    | ASTM D5185m >120 | <b>14</b>    | 40       | 17       |
| Chromium | ppm    | ASTM D5185m >20  | <b>1</b>     | 1        | <1       |
| Nickel   | ppm    | ASTM D5185m >5   | <b>&lt;1</b> | 3        | <1       |
| Titanium | ppm    | ASTM D5185m >2   | <b>&lt;1</b> | 0        | <1       |
| Silver   | ppm    | ASTM D5185m >2   | <b>&lt;1</b> | 0        | 0        |
| Aluminum | ppm    | ASTM D5185m >20  | <b>3</b>     | 11       | 4        |
| Lead     | ppm    | ASTM D5185m >40  | <b>&lt;1</b> | 0        | <1       |
| Copper   | ppm    | ASTM D5185m >330 | <b>2</b>     | 28       | 1        |
| Tin      | ppm    | ASTM D5185m >15  | <b>&lt;1</b> | 1        | <1       |
| Vanadium | ppm    | ASTM D5185m      | <b>&lt;1</b> | 0        | 0        |
| Cadmium  | ppm    | ASTM D5185m      | <b>&lt;1</b> | 0        | <1       |

### ADDITIVES

|            | method | limit/base       | current      | history1 | history2 |
|------------|--------|------------------|--------------|----------|----------|
| Boron      | ppm    | ASTM D5185m 0    | <b>&lt;1</b> | 2        | <1       |
| Barium     | ppm    | ASTM D5185m 0    | <b>0</b>     | 0        | <1       |
| Molybdenum | ppm    | ASTM D5185m 60   | <b>61</b>    | 63       | 53       |
| Manganese  | ppm    | ASTM D5185m 0    | <b>&lt;1</b> | 1        | <1       |
| Magnesium  | ppm    | ASTM D5185m 1010 | <b>933</b>   | 899      | 834      |
| Calcium    | ppm    | ASTM D5185m 1070 | <b>1028</b>  | 1045     | 971      |
| Phosphorus | ppm    | ASTM D5185m 1150 | <b>945</b>   | 935      | 966      |
| Zinc       | ppm    | ASTM D5185m 1270 | <b>1217</b>  | 1188     | 1120     |
| Sulfur     | ppm    | ASTM D5185m 2060 | <b>2865</b>  | 2223     | 3183     |

### CONTAMINANTS

|           | method | limit/base      | current  | history1 | history2 |
|-----------|--------|-----------------|----------|----------|----------|
| Silicon   | ppm    | ASTM D5185m >25 | <b>6</b> | 11       | 5        |
| Sodium    | ppm    | ASTM D5185m     | <b>7</b> | 4        | 6        |
| Potassium | ppm    | ASTM D5185m >20 | <b>2</b> | 28       | 5        |

### INFRA-RED




|           | method   | limit/base      | current     | history1 | history2 |
|-----------|----------|-----------------|-------------|----------|----------|
| Soot %    | %        | *ASTM D7844 >4  | <b>0.3</b>  | 0.7      | 0.3      |
| Nitration | Abs/cm   | *ASTM D7624 >20 | <b>9.4</b>  | 10.8     | 7.6      |
| Sulfation | Abs/.1mm | *ASTM D7415 >30 | <b>19.2</b> | 22.4     | 18.8     |

### FLUID DEGRADATION

|                  | method   | limit/base      | current     | history1 | history2 |
|------------------|----------|-----------------|-------------|----------|----------|
| Oxidation        | Abs/.1mm | *ASTM D7414 >25 | <b>16.4</b> | 20.3     | 15.1     |
| Base Number (BN) | mg KOH/g | ASTM D2896 9.8  | <b>7.8</b>  | 4.9      | 8.7      |







# OIL ANALYSIS REPORT



| VISUAL           | method | limit/base | current | history1 | history2 |
|------------------|--------|------------|---------|----------|----------|
| White Metal      | scalar | *Visual    | NONE    | NONE     | NONE     |
| Yellow Metal     | scalar | *Visual    | NONE    | NONE     | NONE     |
| Precipitate      | scalar | *Visual    | NONE    | NONE     | NONE     |
| Silt             | scalar | *Visual    | NONE    | NONE     | NONE     |
| Debris           | scalar | *Visual    | NONE    | NONE     | NONE     |
| Sand/Dirt        | scalar | *Visual    | NONE    | NONE     | NONE     |
| Appearance       | scalar | *Visual    | NORML   | NORML    | NORML    |
| Odor             | scalar | *Visual    | NORML   | NORML    | NORML    |
| Emulsified Water | scalar | *Visual    | >0.2    | NEG      | NEG      |
| Free Water       | scalar | *Visual    |         | NEG      | NEG      |

| FLUID PROPERTIES | method | limit/base | current | history1 | history2 |
|------------------|--------|------------|---------|----------|----------|
| Visc @ 100°C     | cSt    | ASTM D445  | 15.4    | 13.8     | 13.3     |

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0104441      **Received** : 08 Apr 2024  
**Lab Number** : 06140941      **Tested** : 08 Apr 2024  
**Unique Number** : 10965749      **Diagnosed** : 08 Apr 2024 - Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 410 - Michigan West**  
 39000 Van Born Rd  
 Wayne, MI  
 US 48184

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)