

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Machine Id

GENCOR VIRGIN FEEDER 1

Gearbox

GEAR OIL ISO 220 (5 GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. The fluid was not specified, however, a fluid match indicates that this fluid is (GENERIC) GEAR OIL ISO 220. Please confirm.

Please specify the component make and model with your next sample.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.


Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

				Mar2024		
SAMPLE INFOR	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0087875		
Sample Date		Client Info		04 Mar 2024		
Machine Age	yrs	Client Info		4		
Oil Age	yrs	Client Info		2		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
CONTAMINAT	ION	method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG		
WEAR METAL	S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>200	2		
Chromium	ppm	ASTM D5185m	>10	0		
Nickel	ppm	ASTM D5185m	>10	0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>25	0		
Lead	ppm	ASTM D5185m	>50	0		
Copper	ppm	ASTM D5185m	>200	0		
Tin	ppm	ASTM D5185m	>10	<1		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	50	67		
Barium	ppm	ASTM D5185m	15	0		
Molybdenum	ppm	ASTM D5185m	15	0		
Manganese	ppm	ASTM D5185m		<1		
Magnesium	ppm	ASTM D5185m	50	15		
Calcium	ppm	ASTM D5185m	50	12		
Phosphorus	ppm	ASTM D5185m	350	276		
Zinc	ppm	ASTM D5185m	100	13		
Sulfur	ppm	ASTM D5185m	12500	6940		
CONTAMINAN	TS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>50	8		
Sodium	ppm	ASTM D5185m		<1		
Potassium	ppm	ASTM D5185m	>20	0		
FLUID DEGRAI	DATION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.85	0.38		



OIL ANALYSIS REPORT




VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE	NONE		
Sand/Dirt	scalar	*Visual	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML		
Emulsified Water	scalar	*Visual	>0.2	NEG		
Free Water	scalar	*Visual		NEG		
FLUID PROPE	RTIES	method	limit/base	current	history1	history2

FLUID PROP	ERHES	method			history2
Visc @ 40°C	cSt	ASTM D445	220	213	


Of tivil EE livil tale	 	000		
Color			no image	no image
Bottom			no image	no image

GRAPHS



10	Non-ferrous Metals	
	copper	
(peal passage Pad	
= 6	mananana tin	
ld 2		
		24
	7 (4.1919)	/Jar4/2
		Σ









Certificate 12367

Sample No. Lab Number : 06142378

Test Package : IND 2

: PCA0087875 Unique Number : 10967186

To discuss this sample report, contact Customer Service at 1-800-237-1369.

: WearCheck USA - 501 Madison Ave., Cary, NC 27513

Received **Tested** Diagnosed

: 08 Apr 2024 : 09 Apr 2024

: 09 Apr 2024 - Wes Davis

US 53963 Contact: DAVE KARTECHNER dave@kartechnerbrothers.com T: (920)324-2874

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Contact/Location: DAVE KARTECHNER - KARWAU

KARTECHNERS

WAUPUN, WI

N11829 COUNTY RD I