

# **OIL ANALYSIS REPORT**

### Area ALBERT LEA Machine Id Unit 05 DB010105E

Natural Gas Engine

# PETRO CANADA DURON MONOGRADE HD 40W (350 GAL)

## DIAGNOSIS

#### Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor. ( Customer Sample Comment: 84 Gallons of lube oil added this month.)

#### Wear


All component wear rates are normal.

#### Contamination

Light fuel dilution occurring. No other contaminants were detected in the oil.

#### **Fluid Condition**

The BN result indicates that there is suitable alkalinity remaining in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



SAMPLE INFOR	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0106492	PCA0106491	PCA0106488
Sample Date		Client Info		02 Apr 2024	29 Feb 2024	25 Jan 2024
Machine Age	hrs	Client Info		2646	2323	1872
Oil Age	hrs	Client Info		2646	2323	1872
Oil Changed		Client Info		Not Changd	Not Changd	Oil Added
Sample Status				MARGINAL	MARGINAL	NORMAL
CONTAMINAT	ION	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG	NEG	NEG
WEAR METAL	S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	5	5	11
Chromium	ppm	ASTM D5185m	>4	0	<1	<1
Nickel	ppm	ASTM D5185m	>2	0	0	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>9	1	2	2
Lead	ppm	ASTM D5185m	>30	0	<1	<1
Copper	ppm	ASTM D5185m	>35	2	3	4
Tin	ppm	ASTM D5185m	>4	<1	0	0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	<1	2
Barium	ppm	ASTM D5185m		0	0	5
Molybdenum	ppm	ASTM D5185m		<1	1	1
Manganese	ppm	ASTM D5185m		<1	0	0
Magnesium	ppm	ASTM D5185m		900	954	1314
Calcium	ppm	ASTM D5185m		989	1018	1352
Phosphorus	ppm	ASTM D5185m		1132	1048	1504
Zinc	ppm	ASTM D5185m		1320	1361	1831
Sulfur	ppm	ASTM D5185m		3087	3098	4424
CONTAMINAN	ITS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>+100	5	6	6
Sodium	ppm	ASTM D5185m		2	<1	0
Potassium	ppm	ASTM D5185m	>20	0	1	1
Fuel	%	ASTM D3524	>4.0	<u> </u>	<b>2</b> .1	1.9
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844		0.1	0	0.1
Nitration	Abs/cm	*ASTM D7624	>20	4.1	4.1	4.0
Sulfation	Abs/.1mm	*ASTM D7415	>30	13.3	13.6	13.2
FLUID DEGRA		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	7.2	7.2	7.0
Acid Number (AN)	mg KOH/g	ASTM D8045	-	1.58	1.59	1.43
			0.5	0.00	0.44	0.40


Base Number (BN) mg KOH/g ASTM D2896 8.5


8.10


8.41


8.08
























**FLUID PROPERTIES** method limit/base Visc @ 100°C cSt ASTM D445 14.4 GRAPHS Iron (ppm) 100 80 60 Δr









: WearCheck USA - 501 Madison Ave., Cary, NC 27513

Test Package : MOB 2 (Additional Tests: FuelDilution, PercentFuel)


Received

Diagnosed

Tested

: 08 Apr 2024

: 11 Apr 2024



history1

NONE

NONE

NONE

NONE

NONE

NONE

NORML

NORML

history

NEG

NEG

current

NONE

NONE

NONE

NONE

NONE

NONE

NORML

NORML

current

NEG

NEG

history2

NONE

NONE

NONE

NONE

NONE

NONE


NORML

NORML


history2


NEG

NEG



#### 10.0 (mg KOH/g) 8.0 6. mber 4.0 Base Nu 2.0 0.0





Report Id: MAGGLE [WUSCAR] 06142449 (Generated: 04/11/2024 14:24:49) Rev: 1

Laboratory

Sample No.

Lab Number : 06142449

Unique Number : 10967257

: PCA0106492

Submitted By: Jon Coulter Page 2 of 2