

## **OIL ANALYSIS REPORT**





## DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the fluid.


### Fluid Condition

The condition of the fluid is acceptable for the time in service.

| SAMPLE INFOR     | MATION | method      | limit/base | current        | history1      | history2       |
|------------------|--------|-------------|------------|----------------|---------------|----------------|
| Sample Number    |        | Client Info |            | PCA0029008     |               |                |
| Sample Date      |        | Client Info |            | 07 Apr 2024    |               |                |
| Machine Age      | hrs    | Client Info |            | 595            |               |                |
| Oil Age          | hrs    | Client Info |            | 105            |               |                |
| Oil Changed      |        | Client Info |            | Changed        |               |                |
| Sample Status    |        |             |            | NORMAL         |               |                |
| CONTAMINAT       | ION    | method      | limit/base | current        | history1      | history2       |
| Water            |        | WC Method   | >0.1       | NEG            |               |                |
| WEAR METAL       | S      | method      | limit/base | current        | history1      | history2       |
| Iron             | ppm    | ASTM D5185m | >160       | 94             |               |                |
| Chromium         | ppm    | ASTM D5185m | >5         | <1             |               |                |
| Nickel           | ppm    | ASTM D5185m | >5         | 0              |               |                |
| Titanium         | ppm    | ASTM D5185m |            | <1             |               |                |
| Silver           | ppm    | ASTM D5185m | >5         | 0              |               |                |
| Aluminum         | ppm    | ASTM D5185m | >50        | 2              |               |                |
| Lead             | ppm    | ASTM D5185m | >50        | 42             |               |                |
| Copper           | ppm    | ASTM D5185m | >225       | 82             |               |                |
| Tin              | ppm    | ASTM D5185m | >10        | 7              |               |                |
| Vanadium         | ppm    | ASTM D5185m |            | 0              |               |                |
| Cadmium          | ppm    | ASTM D5185m |            | 0              |               |                |
| ADDITIVES        |        | method      | limit/base | current        | history1      | history2       |
| Boron            | ppm    | ASTM D5185m |            | 357            |               |                |
| Barium           | ppm    | ASTM D5185m |            | <1             |               |                |
| Molybdenum       | ppm    | ASTM D5185m |            | 0              |               |                |
| Manganese        | ppm    | ASTM D5185m |            | <1             |               |                |
| Magnesium        | ppm    | ASTM D5185m |            | 3              |               |                |
| Calcium          | ppm    | ASTM D5185m |            | 243            |               |                |
| Phosphorus       | ppm    | ASTM D5185m |            | 666            |               |                |
| Zinc             | ppm    | ASTM D5185m |            | 6              |               |                |
| Sulfur           | ppm    | ASTM D5185m |            | 3253           |               |                |
| CONTAMINAN       | ITS    | method      | limit/base | current        | history1      | history2       |
| Silicon          | ppm    | ASTM D5185m | >20        | 6              |               |                |
| Sodium           | ppm    | ASTM D5185m |            | 3              |               |                |
| Potassium        | ppm    | ASTM D5185m | >20        | 3              |               |                |
| VISUAL           |        | method      | limit/base | current        | history1      | history2       |
| White Metal      | scalar | *Visual     | NONE       | NONE           |               |                |
| Yellow Metal     | scalar | *Visual     | NONE       | NONE           |               |                |
| Precipitate      | scalar | *Visual     | NONE       | NONE           |               |                |
| Silt             | scalar | *Visual     | NONE       | NONE           |               |                |
| Debris           | scalar | *Visual     | NONE       | NONE           |               |                |
| Sand/Dirt        | scalar | *Visual     | NONE       | NONE           |               |                |
| Appearance       | scalar | *Visual     | NORML      | NORML          |               |                |
| Odor             | scalar | *Visual     | NORML      | NORML          |               |                |
| Emulsified Water | scalar | *Visual     | >0.1       | NEG            |               |                |
| Free Water       | scalar | *Visual     |            | NEG            |               |                |
| 1:51:36) Rev: 1  |        |             |            | Contact/Locati | on: BILL MCAN | IALLY - MILLUM |



# **OIL ANALYSIS REPORT**





To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: MILLUM [WUSCAR] 06145498 (Generated: 04/14/2024 11:51:36) Rev: 1

Certificate 12367

Contact/Location: BILL MCANALLY - MILLUM

wmcanally@millertransgroup.com

F: x:

T: (609)265-2509