


# OIL ANALYSIS REPORT

## Sample Rating Trend



**NORMAL**



Area  
**(97194X) Walgreens - Tractor**  
 Machine Id  
**[Walgreens - Tractor] 136A62105**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 10W30 (11 GAL)**

### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.

#### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

### SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>PCA0118809</b>	PCA0112854	PCA0103834
Sample Date	Client Info		<b>05 Apr 2024</b>	04 Jan 2024	12 Sep 2023
Machine Age	mls	Client Info	<b>479542</b>	448376	418175
Oil Age	mls	Client Info	<b>61367</b>	30201	44009
Oil Changed	Client Info		<b>Changed</b>	Not Changd	Changed
Sample Status			<b>NORMAL</b>	NORMAL	NORMAL

### CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method		<b>NEG</b>	NEG	NEG

### WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >80	<b>30</b>	13	32
Chromium	ppm	ASTM D5185m >5	<b>2</b>	1	2
Nickel	ppm	ASTM D5185m >2	<b>1</b>	<1	0
Titanium	ppm	ASTM D5185m	<b>&lt;1</b>	0	<1
Silver	ppm	ASTM D5185m >3	<b>&lt;1</b>	0	0
Aluminum	ppm	ASTM D5185m >30	<b>15</b>	7	15
Lead	ppm	ASTM D5185m >30	<b>1</b>	<1	0
Copper	ppm	ASTM D5185m >150	<b>6</b>	3	6
Tin	ppm	ASTM D5185m >5	<b>2</b>	<1	<1
Vanadium	ppm	ASTM D5185m	<b>&lt;1</b>	0	0
Cadmium	ppm	ASTM D5185m	<b>&lt;1</b>	0	0

### ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 2	<b>0</b>	2	3
Barium	ppm	ASTM D5185m 0	<b>&lt;1</b>	0	0
Molybdenum	ppm	ASTM D5185m 50	<b>64</b>	63	65
Manganese	ppm	ASTM D5185m 0	<b>1</b>	<1	<1
Magnesium	ppm	ASTM D5185m 950	<b>896</b>	993	1049
Calcium	ppm	ASTM D5185m 1050	<b>1088</b>	1100	1165
Phosphorus	ppm	ASTM D5185m 995	<b>1059</b>	1095	1021
Zinc	ppm	ASTM D5185m 1180	<b>1166</b>	1382	1291
Sulfur	ppm	ASTM D5185m 2600	<b>2590</b>	3025	3159

### CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >20	<b>6</b>	4	5
Sodium	ppm	ASTM D5185m	<b>1</b>	2	4
Potassium	ppm	ASTM D5185m >20	<b>3</b>	<1	2




### INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	<b>0.9</b>	0.5	0.8
Nitration	Abs/cm	*ASTM D7624 >20	<b>11.6</b>	8.8	9.6
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>25.3</b>	21.1	22.7

### FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>23.3</b>	17.8	19.3
Base Number (BN)	mg KOH/g	ASTM D2896	<b>4.2</b>	6.3	5.7





# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	12.00	11.3	11.0

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0118809  
**Lab Number** : 06146856  
**Unique Number** : 10976934  
**Test Package** : FLEET  
**Received** : 12 Apr 2024  
**Tested** : 15 Apr 2024  
**Diagnosed** : 15 Apr 2024 - Wes Davis

**Transervice - Shop 1364 - Berkeley-Mt. Vernon**  
 5100 Lake Terrace NE  
 Mt. Vernon, IL  
 US 62864  
 Contact: Erien White  
 ewhite@transervice.com  
 T: (618)244-8726  
 F: (618)244-8791

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)