

OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id **256010** Component **Gasoline Engine** Fluid **{not provided} (--- GAL)**

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFOR	ΜΔΤΙΩΝ	method	limit/base	current	history1	history2
Sample Number		Client Info	in the babb	GFL0116565		motory
Sample Date		Client Info		10 Apr 2024		
Machine Age	hrs	Client Info		232258		
Oil Age	hrs	Client Info		232258		
Oil Changed	1115	Client Info		Not Changd		
Sample Status				NORMAL		
-				-		
CONTAMINAT	ION	method	limit/base	current	history1	history2
Fuel		WC Method	>4.0	<1.0		
Water		WC Method	>0.2	NEG		
Glycol		WC Method		NEG		
WEAR METAL	S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>150	29		
Chromium	ppm	ASTM D5185m	>20	1		
Nickel	ppm	ASTM D5185m	>5	1		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m	>2	0		
Aluminum	ppm	ASTM D5185m	>40	4		
Lead	ppm	ASTM D5185m	>50	2		
Copper	ppm	ASTM D5185m	>155	1		
Tin	ppm	ASTM D5185m	>10	1		
Vanadium	ppm	ASTM D5185m		<1		
Cadmium	ppm	ASTM D5185m		<1		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		20		
Barium	ppm	ASTM D5185m		<1		
Molybdenum	ppm	ASTM D5185m		274		
Manganese	ppm	ASTM D5185m		3		
Magnesium	ppm	ASTM D5185m		442		
Calcium	ppm	ASTM D5185m		1354		
Phosphorus	ppm	ASTM D5185m		605		
Zinc	ppm	ASTM D5185m		738		
Sulfur	ppm	ASTM D5185m		2163		
CONTAMINAN	ITS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>30	23		
Sodium	ppm	ASTM D5185m	>400	11		
Potassium	ppm	ASTM D5185m	>20	4		
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844		0		
Nitration	Abs/cm	*ASTM D7624	>20	13.9		
Sulfation	Abs/.1mm	*ASTM D7415	>30	24.4		
FLUID DEGRA	DATION	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	20.4		
Base Number (BN)	mg KOH/g	ASTM D2896		3.5		



OIL ANALYSIS REPORT

35 T		VISUAL		method	limit/base	current	history1	history2
Oxidation		White Metal	scalar	*Visual	NONE	NONE		
suffation		Yellow Metal	scalar	*Visual	NONE	NONE		
E 25 - G		Precipitate	scalar	*Visual	NONE	NONE		
₽ 20-		Silt	scalar	*Visual	NONE	NONE		
15-		Debris	scalar	*Visual	NONE	NONE		
10		Sand/Dirt	scalar	*Visual	NONE	NONE		
Apr10/24	Apr1 0/24	Appearance	scalar	*Visual	NORML	NORML		
Apri	Apri	Odor	scalar	*Visual	NORML	NORML		
Base Number		Emulsified Water	scalar	*Visual	>0.2	NEG		
4.0		Free Water	scalar	*Visual		NEG		
35		FLUID PROPE	RTIES	method	limit/base	current	history1	history2
5 2.0 -		Visc @ 100°C	cSt	ASTM D445		11.1		
1.5		GRAPHS						
0.5	_	Ferrous Alloys						
0.0	30	iron						
Apr10/24	ç 25	5 - chromium						
Apr	20	D						
Viscosity @ 100°C	E 15							
14 T								
13 - Abnormal	10) -						
ç ¹²		5-						
C12 C12 11 11 12 11 11 11 11 11 11	(, L						
³ 10 Abnormal		Apr1 0/24			Apr10/24			
9 Abnormal		Apr			Apr			
8	< 1/	Non-ferrous Meta	ls					
Apr10/24	ē 10	copper						
Ar	Y K	B - management lead						
	u dd							
		1						
		2						
	4							
	(4			
		sr10/24			kpr10/24			
					A			
	14	Viscosity @ 100°C	-			Base Number		
	1.	*T :				- Babe Maniber		
					4.0			1
	13	³ [•] Abnormal			3.5			
	13	³ [•] Abnormal			3.5			
	13	³ [•] Abnormal			3.5 (B) 3.0 HOX 2.5 k 2.0			
	13	3- Abnormal 2- 1-			3.5 (B) 3.0 B(D) 2.5 (B) 2.0 (B) 2.1 (B) 2.0 (B) 1.5			
	12 (24001) 143	3- Abnormal 2- 1-			3.5 (B) 3.0 HOX 2.5 k 2.0			
	12 (24001) 143	- Abnormal			3.5 (B) 3.0 B(D) 2.5 (B) 2.0 (B) 2.1 (B) 2.0 (B) 1.5			
	12 (24001) 143	Abnormal			3.5 (HO) DU Jaquuny Use 1.0 0.5 0.0			
	12 (24001) 143	Abnormal			3.5 (HO) DU Jaquuny Use 1.0 0.5 0.0			n1024
	12 (24001) 143	- Abnormal			3.5 (9)(0) 3.0 (0)(0) 22.5 (0)(1) 3.0 (0)(1) 22.0 (0)(1) 3.0 (0)(1) 3.0 (0)(1)(1)(1)(1)(1)(1)(1)(1)(1)(1)(1)(1)(1)			Auri 0.24
Certificate L2367	Laboratory : W Sample No. : G Lab Number : 10 Unique Number : 11 Test Package : Fi	Abnormal Abnormal Abnormal Abnormal Abnormal FL0116565 6147964 0978042 LEET	Recei Teste Diagn	ved : 12 d : 15 losed : 15	3.5 (1)(1)(1)(1)(1)(1)(1)(1)(1)(1)(1)(1)(1)(6FL Envir	Fred Contact: \	lericksburg Haulin 4 Houser Drive ericksburg, V/ US 2240 WILLIAM MILC
Certificate L2367 To discuss this s	Laboratory : W Sample No. : G Lab Number : 10 Unique Number : 10 Test Package : Fl sample report, cor	Abnormal Abn	Recei Teste Diagn	ved : 12 d : 15 losed : 15	3.5 (9)(0) 00 00 2.5 (0) 00 00 00 2.5 (0) 00 00 00 1.5 (0) 00 00 00 00 (0) 00 00 00 00 (0) 0	6FL Envir	1095 Fred Contact: N	l ericksburg Haulin 4 Houser Driv ericksburg, V US 2240

Report Id: GFL652 [WUSCAR] 06147964 (Generated: 04/15/2024 12:15:15) Rev: 1

Submitted By: TECHNICIAN ACCOUNT