


# OIL ANALYSIS REPORT

**Sample Rating Trend**

**NORMAL**


Area

**Dairy Farms of America-Yard Horse**
**[Dairy Farms of America-Yard Horse] 268A524001**

Machine Id

**Diesel Engine**

Component

**PETRO CANADA DURON SHP 10W30 (--- GAL)**
**DIAGNOSIS**
**Recommendation**

Resample at the next service interval to monitor.

**Wear**

Metal levels are typical for a components first oil change.

**Contamination**

There is no indication of any contamination in the oil.

**Fluid Condition**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

**SAMPLE INFORMATION**

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>PCA0103915</b>	---	---
Sample Date	Client Info		<b>26 Feb 2024</b>	---	---
Machine Age	hrs	Client Info	<b>949</b>	---	---
Oil Age	hrs	Client Info	<b>949</b>	---	---
Oil Changed	Client Info		<b>Changed</b>	---	---
Sample Status			<b>NORMAL</b>	---	---

**CONTAMINATION**

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<b>&lt;1.0</b>	---	---
Water	WC Method	>0.2	<b>NEG</b>	---	---
Glycol	WC Method		<b>NEG</b>	---	---

**WEAR METALS**

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >100	<b>75</b>	---	---
Chromium	ppm	ASTM D5185m >20	<b>2</b>	---	---
Nickel	ppm	ASTM D5185m >4	<b>&lt;1</b>	---	---
Titanium	ppm	ASTM D5185m	<b>&lt;1</b>	---	---
Silver	ppm	ASTM D5185m >3	<b>0</b>	---	---
Aluminum	ppm	ASTM D5185m >20	<b>6</b>	---	---
Lead	ppm	ASTM D5185m >40	<b>&lt;1</b>	---	---
Copper	ppm	ASTM D5185m >330	<b>86</b>	---	---
Tin	ppm	ASTM D5185m >15	<b>&lt;1</b>	---	---
Vanadium	ppm	ASTM D5185m	<b>0</b>	---	---
Cadmium	ppm	ASTM D5185m	<b>&lt;1</b>	---	---

**ADDITIVES**

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 2	<b>70</b>	---	---
Barium	ppm	ASTM D5185m 0	<b>4</b>	---	---
Molybdenum	ppm	ASTM D5185m 50	<b>53</b>	---	---
Manganese	ppm	ASTM D5185m 0	<b>4</b>	---	---
Magnesium	ppm	ASTM D5185m 950	<b>761</b>	---	---
Calcium	ppm	ASTM D5185m 1050	<b>1260</b>	---	---
Phosphorus	ppm	ASTM D5185m 995	<b>816</b>	---	---
Zinc	ppm	ASTM D5185m 1180	<b>918</b>	---	---
Sulfur	ppm	ASTM D5185m 2600	<b>2582</b>	---	---

**CONTAMINANTS**

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<b>22</b>	---	---
Sodium	ppm	ASTM D5185m	<b>14</b>	---	---
Potassium	ppm	ASTM D5185m >20	<b>4</b>	---	---




**INFRA-RED**

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	<b>1</b>	---	---
Nitration	Abs/cm	*ASTM D7624 >20	<b>10.4</b>	---	---
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>21.4</b>	---	---

**FLUID DEGRADATION**

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>18.9</b>	---	---
Base Number (BN)	mg KOH/g	ASTM D2896	<b>8.2</b>	---	---





# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2	
White Metal	scalar	*Visual	NONE	NONE	---	---
Yellow Metal	scalar	*Visual	NONE	NONE	---	---
Precipitate	scalar	*Visual	NONE	NONE	---	---
Silt	scalar	*Visual	NONE	NONE	---	---
Debris	scalar	*Visual	NONE	NONE	---	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---	---
Appearance	scalar	*Visual	NORML	NORML	---	---
Odor	scalar	*Visual	NORML	NORML	---	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---	---
Free Water	scalar	*Visual		NEG	---	---

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	12.00	11.9	---	---

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0103915      **Received** : 15 Apr 2024  
**Lab Number** : **06148437**      **Tested** : 16 Apr 2024  
**Unique Number** : 10978515      **Diagnosed** : 16 Apr 2024 - Wes Davis  
**Test Package** : FLEET

**Transervice - Shop 2680 - LeMars**  
 1330 12th Ave SW  
 LeMars, IA  
 US 51031

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Contact: Stacey Rabey  
 srabey@transervice.com  
 T: (712)501-9908  
 F: