


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
631634
 Component
Diesel Engine
 Fluid
PETRO CANADA DURON SHP 10W30 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

Wear

Metal levels are typical for a new component breaking in.

Contamination

Elevated aluminum (Al) and/or lead (Pb) and potassium (K) levels in your metals analysis are likely a result of solder flux release into the lubricant and is common on new equipment/components. There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			PCA0121432	PCA0112232	PCA0102921
Sample Date	Client Info			09 Apr 2024	01 Dec 2023	07 Aug 2023
Machine Age	mls	Client Info		3076	59096	30519
Oil Age	mls	Client Info		3076	28577	0
Oil Changed	Client Info			Changed	Changed	Not Changed
Sample Status				NORMAL	NORMAL	NORMAL

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>5		<1.0	<1.0	<1.0
Water	WC Method	>0.2		NEG	NEG	NEG
Glycol	WC Method			NEG	NEG	NEG

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	45	87	54
Chromium	ppm	ASTM D5185m	>20	3	6	4
Nickel	ppm	ASTM D5185m	>4	0	2	<1
Titanium	ppm	ASTM D5185m		11	2	<1
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>20	47	166	145
Lead	ppm	ASTM D5185m	>40	0	<1	<1
Copper	ppm	ASTM D5185m	>330	65	162	181
Tin	ppm	ASTM D5185m	>15	2	5	4
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	<1	0




ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	2	15	18	27
Barium	ppm	ASTM D5185m	0	0	13	2
Molybdenum	ppm	ASTM D5185m	50	54	49	46
Manganese	ppm	ASTM D5185m	0	2	6	5
Magnesium	ppm	ASTM D5185m	950	893	619	565
Calcium	ppm	ASTM D5185m	1050	1454	1649	1624
Phosphorus	ppm	ASTM D5185m	995	1066	747	746
Zinc	ppm	ASTM D5185m	1180	1310	938	909
Sulfur	ppm	ASTM D5185m	2600	2944	2053	2032

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	7	13	9
Sodium	ppm	ASTM D5185m		3	5	5
Potassium	ppm	ASTM D5185m	>20	102	373	302

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	0.9	1.3	0.6
Nitration	Abs/cm	*ASTM D7624	>20	9.3	11.6	9.3
Sulfation	Abs/.1mm	*ASTM D7415	>30	21.7	25.0	23.0

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	18.4	26.3	22.2
Base Number (BN)	mg KOH/g	ASTM D2896		7.2	6.0	7.8









OIL ANALYSIS REPORT



PARAMETER	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	12.00	11.4	11.3

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0121432 **Received** : 16 Apr 2024
Lab Number : 06150076 **Tested** : 17 Apr 2024
Unique Number : 10980154 **Diagnosed** : 17 Apr 2024 - Wes Davis
Test Package : MOB 1 (Additional Tests: TBN)

MILLER TRUCK LEASING #118
 2196 BENNETT ROAD
 PHILADELPHIA, PA
 US 19116

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Contact: ROSTY VITER
 rviter@millertransgroup.com
 T: (215)552-9832
 F: (215)552-9892