




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**928092-260349**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>GFL0114197</b>	GFL0114127	GFL0108075
Sample Date	Client Info	<b>04 Apr 2024</b>	07 Mar 2024	08 Feb 2024
Machine Age	hrs Client Info	<b>1968</b>	24110	23962
Oil Age	hrs Client Info	<b>23697</b>	24110	23697
Oil Changed	Client Info	<b>Changed</b>	Not Changd	Not Changd
Sample Status		<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method >0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method	<b>NEG</b>	NEG	NEG

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >100	<b>19</b>	17	11
Chromium	ppm ASTM D5185m >20	<b>&lt;1</b>	<1	1
Nickel	ppm ASTM D5185m >4	<b>0</b>	0	<1
Titanium	ppm ASTM D5185m	<b>0</b>	0	<1
Silver	ppm ASTM D5185m >3	<b>0</b>	0	<1
Aluminum	ppm ASTM D5185m >20	<b>2</b>	2	1
Lead	ppm ASTM D5185m >40	<b>&lt;1</b>	0	<1
Copper	ppm ASTM D5185m >330	<b>6</b>	1	1
Tin	ppm ASTM D5185m >15	<b>&lt;1</b>	0	<1
Vanadium	ppm ASTM D5185m	<b>&lt;1</b>	0	<1
Cadmium	ppm ASTM D5185m	<b>0</b>	0	<1

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	<b>&lt;1</b>	2	1
Barium	ppm ASTM D5185m 0	<b>0</b>	0	0
Molybdenum	ppm ASTM D5185m 60	<b>57</b>	56	59
Manganese	ppm ASTM D5185m 0	<b>&lt;1</b>	<1	<1
Magnesium	ppm ASTM D5185m 1010	<b>920</b>	890	920
Calcium	ppm ASTM D5185m 1070	<b>1069</b>	1002	1036
Phosphorus	ppm ASTM D5185m 1150	<b>1032</b>	976	994
Zinc	ppm ASTM D5185m 1270	<b>1199</b>	1176	1180
Sulfur	ppm ASTM D5185m 2060	<b>3288</b>	2862	3352

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	<b>4</b>	6	6
Sodium	ppm ASTM D5185m	<b>6</b>	3	0
Potassium	ppm ASTM D5185m >20	<b>15</b>	0	1

## INFRA-RED

method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	<b>1</b>	0.8	0.6
Nitration	Abs/cm *ASTM D7624 >20	<b>8.4</b>	8.1	7.0
Sulfation	Abs/.1mm *ASTM D7415 >30	<b>20.5</b>	19.9	19.2


## FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	<b>15.6</b>	15.0	14.1
Base Number (BN)	mg KOH/g ASTM D2896 9.8	<b>7.9</b>	8.2	8.3




# OIL ANALYSIS REPORT


FT-IR (Direct Trend)



Base Number



Viscosity @ 100°C




VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG


FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	13.7	13.9

## GRAPHS


Ferrous Alloys




Non-ferrous Metals



Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
 Sample No. : GFL0114197  
 Lab Number : 06150917  
 Unique Number : 10980995  
 Test Package : FLEET

Received : 16 Apr 2024  
 Tested : 17 Apr 2024  
 Diagnosed : 17 Apr 2024 - Wes Davis

GFL Environmental - 837 - Harrison TS  
 22820 S State Route 291  
 Harrisonville, MO  
 US 64701  
 Contact: SARA PATRICK  
 spatrack@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: