




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id

713013

Component

Diesel Engine

Fluid

PETRO CANADA DURON SHP 15W40 (--- QTS)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

Metal levels are typical for a new component breaking in.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		GFL0077754	GFL0077810	GFL0077812
Sample Date	Client Info		10 Apr 2024	17 Oct 2023	09 Oct 2023
Machine Age	hrs	Client Info	951	380	352
Oil Age	hrs	Client Info	0	0	352
Oil Changed	Client Info		Changed	Not Changd	Changed
Sample Status			NORMAL	NORMAL	ABNORMAL

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>3.0	<1.0	<1.0	0.4
Water	WC Method	>0.2	NEG	NEG	NEG
Glycol	WC Method		NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >65	22	4	36
Chromium	ppm	ASTM D5185m >5	<1	<1	1
Nickel	ppm	ASTM D5185m >3	10	1	5
Titanium	ppm	ASTM D5185m >5	0	0	<1
Silver	ppm	ASTM D5185m >2	<1	<1	1
Aluminum	ppm	ASTM D5185m >35	6	2	15
Lead	ppm	ASTM D5185m >10	0	<1	<1
Copper	ppm	ASTM D5185m >180	44	18	47
Tin	ppm	ASTM D5185m >8	<1	1	3
Vanadium	ppm	ASTM D5185m	<1	0	<1
Cadmium	ppm	ASTM D5185m	0	0	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	15	47	306
Barium	ppm	ASTM D5185m 0	<1	0	12
Molybdenum	ppm	ASTM D5185m 60	63	66	114
Manganese	ppm	ASTM D5185m 0	1	<1	4
Magnesium	ppm	ASTM D5185m 1010	918	933	654
Calcium	ppm	ASTM D5185m 1070	1088	1099	1392
Phosphorus	ppm	ASTM D5185m 1150	944	1037	694
Zinc	ppm	ASTM D5185m 1270	1138	1246	850
Sulfur	ppm	ASTM D5185m 2060	3208	3144	2363

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >15	14	18	▲ 102
Sodium	ppm	ASTM D5185m	3	2	4
Potassium	ppm	ASTM D5185m >20	15	5	45

INFRA-RED




	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	0.2	0.1	0.1
Nitration	Abs/cm	*ASTM D7624 >20	8.5	5.0	7.5
Sulfation	Abs/.1mm	*ASTM D7415 >30	20.0	18.3	24.3

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	16.6	14.4	20.4
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	6.5	9.2	8.5







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	12.6	13.3	9.9

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0077754 **Received** : 16 Apr 2024
Lab Number : 06151025 **Tested** : 17 Apr 2024
Unique Number : 10981103 **Diagnosed** : 17 Apr 2024 - Wes Davis
Test Package : FLEET

GFL Environmental - 650 - West Point Hauling
 7825 Parham Landing Road
 West Point, VA
 US 23181
 Contact: Jason Smith
 jasonsmith@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)