




# OIL ANALYSIS REPORT

Sample Rating Trend



FUEL



Machine Id  
**10442 AUTOCAR ACX**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON SHP 15W40 (48 GAL)**

## DIAGNOSIS

### Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

Light fuel dilution occurring. No other contaminants were detected in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>GFL0117450</b>	GFL0103194	GFL0094646
Sample Date	Client Info	<b>16 Apr 2024</b>	29 Feb 2024	05 Dec 2023
Machine Age	hrs	<b>0</b>	6757	6176
Oil Age	hrs	<b>0</b>	0	0
Oil Changed	Client Info	<b>N/A</b>	Not Changd	Not Changd
Sample Status		<b>MARGINAL</b>	ABNORMAL	ABNORMAL

## CONTAMINATION

method	limit/base	current	history1	history2
Water	WC Method >0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method	<b>NEG</b>	NEG	NEG

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >75	<b>12</b>	41	11
Chromium	ppm ASTM D5185m >5	<b>&lt;1</b>	2	<1
Nickel	ppm ASTM D5185m >4	<b>0</b>	0	0
Titanium	ppm ASTM D5185m >2	<b>0</b>	0	<1
Silver	ppm ASTM D5185m >2	<b>0</b>	0	0
Aluminum	ppm ASTM D5185m >15	<b>3</b>	8	5
Lead	ppm ASTM D5185m >25	<b>0</b>	<1	0
Copper	ppm ASTM D5185m >100	<b>0</b>	12	10
Tin	ppm ASTM D5185m >4	<b>&lt;1</b>	<1	0
Vanadium	ppm ASTM D5185m	<b>0</b>	0	<1
Cadmium	ppm ASTM D5185m	<b>0</b>	0	<1

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	<b>3</b>	3	4
Barium	ppm ASTM D5185m 0	<b>0</b>	0	0
Molybdenum	ppm ASTM D5185m 60	<b>59</b>	55	54
Manganese	ppm ASTM D5185m 0	<b>0</b>	<1	<1
Magnesium	ppm ASTM D5185m 1010	<b>968</b>	861	917
Calcium	ppm ASTM D5185m 1070	<b>1114</b>	948	995
Phosphorus	ppm ASTM D5185m 1150	<b>1058</b>	880	1016
Zinc	ppm ASTM D5185m 1270	<b>1265</b>	1163	1215
Sulfur	ppm ASTM D5185m 2060	<b>3446</b>	2464	2885

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	<b>3</b>	5	8
Sodium	ppm ASTM D5185m	<b>2</b>	9	4
Potassium	ppm ASTM D5185m >20	<b>3</b>	15	1
Fuel	% ASTM D3524 >3.0	<b>▲ 1.0</b>	▲ 6.3	▲ 5.8

## INFRA-RED





method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >6	<b>0.9</b>	1.9	0.6
Nitration	Abs/cm *ASTM D7624 >20	<b>8.3</b>	13.2	6.8
Sulfation	Abs/.1mm *ASTM D7415 >30	<b>20.8</b>	26.2	19.2

## FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	<b>15.9</b>	22.4	14.5
Base Number (BN)	mg KOH/g ASTM D2896 9.8	<b>9.3</b>	7.2	9.0







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	14.4	13.0

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0117450 **Received** : 17 Apr 2024  
**Lab Number** : 06151694 **Tested** : 22 Apr 2024  
**Unique Number** : 10981772 **Diagnosed** : 22 Apr 2024 - Wes Davis  
**Test Package** : FLEET ( Additional Tests: PercentFuel )

**GFL Environmental - 001 - Raleigh(CNG)**  
 3741 Conquest Drive  
 Garner, NC  
 US 27529  
 Contact: Ronald Gregory  
 rgregory@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)