

OIL ANALYSIS REPORT

Sample Rating Trend





Area G.LOPES CONSTRUCTION INC./Off-Road

Component Front Right Planetary

{not provided} (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORI	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0122675		
Sample Date		Client Info		17 Apr 2024		
Machine Age	hrs	Client Info		34603		
Oil Age	hrs	Client Info		34603		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
CONTAMINAT	ION	method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG		
WEAR METAL	S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>500	95		
Chromium	ppm	ASTM D5185m	>10	<1		
Nickel	ppm	ASTM D5185m	>10	0		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>25	2		
Lead	ppm	ASTM D5185m	>25	1		
Copper	ppm	ASTM D5185m	>75	6		
Tin	ppm	ASTM D5185m	>10	<1		
Vanadium	ppm	ASTM D5185m		<1		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		<1		
Manganese	ppm	ASTM D5185m		<1		
Magnesium	ppm	ASTM D5185m		12		
Calcium	ppm	ASTM D5185m		3103		
Phosphorus	ppm	ASTM D5185m		979		
Zinc	ppm	ASTM D5185m		1103		
Sulfur	ppm	ASTM D5185m		7641		
CONTAMINAN	TS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>75	11		
Sodium	ppm	ASTM D5185m		2		
Potassium	ppm	ASTM D5185m	>20	0		
FLUID DEGRA	DATION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		1.43		



OIL ANALYSIS REPORT

VISUAL



		V	Vhite Metal	scalar	*Visual	NONE		NONE		
		Y	ellow Metal	scalar	*Visual	NONE		NONE		
		Р	recipitate	scalar	*Visual	NONE		NONE		
		S	ilt	scalar	*Visual	NONE		NONE		
		D	ebris	scalar	*Visual	NONE		NONE		
		S	and/Dirt	scalar	*Visual	NONE		NONE		
	Apr17/24	A	ppearance	scalar	*Visual	NORML		NORML		
	Apr	С	dor	scalar	*Visual	NORML		NORML		
		E	mulsified Water	scalar	*Visual	>0.2		NEG		
		F	ree Water	scalar	*Visual			NEG		
			FLUID PROPE	RTIES	method	limit/bas	se	current	history1	history2
		V	′isc @ 40°C	cSt	ASTM D445			186		
			SAMPLE IMAG	ES	method	limit/bas	se	current	history1	history2
	Apr17/24	С	Color					no image	no image	no image
		в	ottom					no image	no image	no image
	1	2000 - 특 1000 -	GRAPHS Iron (ppm) Severe Abnormal				150 = 100 = 50	Lead (ppm) Severe		
		Aluminum (ppm			Apr17/24	30 T	Chromium (p	pm)		
					Apr17/24	20- 10- 0-	Apromal			
		²⁰⁰ T	Copper (ppm) Severe			- Apri		Silicon (ppm)		
		튭 100 0	Abnormal				200- 100- 0-	Abnormal		
			Viscosity @ 40°C			Apr17/24		Acid Number		
		()_0 150 0€) ಸ್ವ 100 50	Abnormal Abnormal				400 Jumper (mg KOH/g)			
			Apr17/24			Apr17/24	Ach	Apr17/24		
	Laboratory Sample No. Lab Number Unique Number	: PC : <mark>06</mark> : 10	A0122675 <mark>154616</mark> 990039	Rece Teste	Madison Ave., Cary, NC Received : 19 Apr Tested : 22 Apr Diagnosed : 23 Apr 2		2024		G LOPES CONSTRUCTIO 565 WINTHROP S TAUNTON, M US 0278	
discuss this s	methods that	cont are o	act Customer Servi outside of the ISO 1	7025 scc	pe of accre					CH MCGRATI h@glopes.cor T
Denotes test	methods that onformity to sp					ditation.				

> Submitted By: MATT MANOLI Page 2 of 2