

# **OIL ANALYSIS REPORT**

Sample Rating Trend

FUEL

# (DXF671) 10628

Area

## Diesel Engine

Fluid

## PETRO CANADA DURON SHP 15W40 (28 QTS)

### DIAGNOSIS

#### Recommendation

We recommend that you drain the oil from the component if this has not already been done. We recommend an early resample to monitor this condition.

#### Wear

All component wear rates are normal.

#### Contamination

There is a moderate amount of fuel present in the oil. Tests confirm the presence of fuel in the oil.


#### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The oil is no longer serviceable due to the presence of contaminants.


<b>3</b> 15)		il2016 Feb20	19 Aug2020 Feb2021 Au	g2022 Feb2023 Apr2023 Oct2023	3 Mar2024	
SAMPLE INFOR	RMATION	method	limit/base	current	history1	history2
Sample Number		Client Info		GFL0111488	GFL0111460	GFL0068819
Sample Date		Client Info		17 Apr 2024	29 Mar 2024	06 Mar 2024
Machine Age	hrs	Client Info		20795	20511	20217
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Not Changd	Not Changd	Changed
Sample Status				ABNORMAL	ABNORMAL	ATTENTION
CONTAMINA	TION	method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
WEAR META	LS	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>75	22	10	2
Chromium	ppm	ASTM D5185m	>5	1	<1	<1
Nickel	ppm	ASTM D5185m	>4	<1	0	<1
Titanium	ppm	ASTM D5185m	>2	<1	0	<1
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>15	3	1	2
Lead	ppm	ASTM D5185m	>25	<1	0	3
Copper	ppm	ASTM D5185m	>100	3	2	6
Tin	ppm	ASTM D5185m	>4	<1	<1	0
Vanadium	ppm	ASTM D5185m		<1	0	<1
Cadmium	ppm	ASTM D5185m		<1	0	<1
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	14	17	60
Barium	ppm	ASTM D5185m	0	0	0	0
Molybdenum	ppm	ASTM D5185m	60	48	46	39
Manganese	ppm	ASTM D5185m	0	<1	<1	<1
Magnesium	ppm	ASTM D5185m	1010	715	753	481
Calcium	ppm	ASTM D5185m	1070	883	888	<b>1</b> 447
Phosphorus	ppm	ASTM D5185m	1150	818	846	705
Zinc	ppm	ASTM D5185m	1270	945	976	851
Sulfur	ppm	ASTM D5185m	2060	2683	2986	2398
CONTAMINA	NTS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	14	11	11
Sodium	ppm	ASTM D5185m		4	3	3
Potassium	ppm	ASTM D5185m	>20	2	0	2
Fuel	%	ASTM D3524	>3.0	<b>A</b> 3.7	▲ 3.4	▲ 2.2
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>6	0.3	0.2	0.1
Nitration	Abs/cm	*ASTM D7624	>20	6.4	5.7	4.7
Sulfation	Abs/.1mm	*ASTM D7415	>30	19.0	18.1	20.5
FLUID DEGRA		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	15.6	15.0	17.5
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	7.4	7.7	9.1





# **OIL ANALYSIS REPORT**














VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPE	RTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	<b>11.6</b>	<b>1</b> 1.8	12.1
GRAPHS						

Ferrous Alloys

Non-ferrous Metals







Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513 GFL Environmental - 073 - Warner Robins - Transwaste Sample No. : GFL0111488 Received : 19 Apr 2024 155 Story Road Lab Number : 06155051 Tested : 23 Apr 2024 Warner Robins, GA US 31093 Unique Number : 10990474 Diagnosed : 23 Apr 2024 - Wes Davis Test Package : FLEET ( Additional Tests: PercentFuel ) Contact: Mike Taft Certificate 12367 To discuss this sample report, contact Customer Service at 1-800-237-1369. T: \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012) F:

Report Id: GFL073 [WUSCAR] 06155051 (Generated: 04/24/2024 09:27:55) Rev: 1

Submitted By: JOSH MALONEY

Page 2 of 2