






PROBLEM SUMMARY

Area
(EIB906)
 Machine Id
3665
 Component
Diesel Engine
 Fluid
PETRO CANADA DURON SHP 15W40 (11 GAL)

Sample Rating Trend



COMPONENT CONDITION SUMMARY



RECOMMENDATION

We advise that you check the fuel injection system. We recommend that you drain the oil from the component if this has not already been done. We recommend an early resample to monitor this condition.

PROBLEMATIC TEST RESULTS

Sample Status				SEVERE	ATTENTION	SEVERE
Fuel	%	ASTM D3524	>3.0	▲ 15.2	▲ 1.5	▲ 23.9
Visc @ 100°C	cSt	ASTM D445	15.4	▲ 9.9	12.4	▲ 8.1

Customer Id: GFL094
 Sample No.: GFL0072139
 Lab Number: 06155593
 Test Package: FLEET



To manage this report scan the QR code

To discuss the diagnosis or test data:
 Wes Davis +1 905-569-8600 x223
wesd@wearcheck.ca

To change component or sample information:
 Customer Service +1 1-800-237-1369
customerservice@wearcheck.com

RECOMMENDED ACTIONS

Action	Status	Date	Done By	Description
Change Fluid	---	---	?	We recommend that you drain the oil from the component if this has not already been done.
Resample	---	---	?	We recommend an early resample to monitor this condition.
Check Fuel/injector System	---	---	?	We advise that you check the fuel injection system.

HISTORICAL DIAGNOSIS

FUEL



15 Jan 2024 Diag: Wes Davis

The oil change at the time of sampling has been noted. Confirm the source of the lubricant being utilized for top-up/fill. Resample at the next service interval to monitor. No other corrective action is recommended at this time. All component wear rates are normal. Light fuel dilution occurring. No other contaminants were detected in the oil. Additive levels indicate the addition of a different brand, or type of oil. The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

view report



FUEL



18 Jul 2023 Diag: Wes Davis

We advise that you check the fuel injection system. The oil change at the time of sampling has been noted. We recommend an early resample to monitor this condition. Metal levels are typical for a new component breaking in. There is a high amount of fuel present in the oil. Tests confirm the presence of fuel in the oil. The BN result indicates that there is suitable alkalinity remaining in the oil. Fuel is present in the oil and is lowering the viscosity. The oil is no longer serviceable due to the presence of contaminants.

view report



FUEL



16 May 2023 Diag: Wes Davis

The oil change at the time of sampling has been noted. We recommend an early resample to monitor this condition. All component wear rates are normal. There is a moderate amount of fuel present in the oil. Tests confirm the presence of fuel in the oil. The BN result indicates that there is suitable alkalinity remaining in the oil. Fuel is present in the oil and is lowering the viscosity. The oil is no longer serviceable due to the presence of contaminants.


view report





OIL ANALYSIS REPORT

Sample Rating Trend



FUEL



Area
(EIB906)
 Machine Id
3665
 Component
Diesel Engine
 Fluid
PETRO CANADA DURON SHP 15W40 (11 GAL)

DIAGNOSIS

▲ Recommendation

We advise that you check the fuel injection system. We recommend that you drain the oil from the component if this has not already been done. We recommend an early resample to monitor this condition.

Wear

All component wear rates are normal.

▲ Contamination

There is a high amount of fuel present in the oil. Tests confirm the presence of fuel in the oil.

▲ Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. Fuel is present in the oil and is lowering the viscosity. The oil is no longer serviceable due to the presence of contaminants.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		GFL0072139	GFL0072108	GFL0074590
Sample Date	Client Info		17 Apr 2024	15 Jan 2024	18 Jul 2023
Machine Age	hrs	Client Info	20643	20299	20178
Oil Age	hrs	Client Info	344	600	20178
Oil Changed	Client Info		Not Chngd	Changed	Changed
Sample Status			SEVERE	ATTENTION	SEVERE

CONTAMINATION

	method	limit/base	current	history1	history2
Water	WC Method	>0.2	NEG	NEG	NEG
Glycol	WC Method		NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >75	21	7	20
Chromium	ppm	ASTM D5185m >5	1	<1	1
Nickel	ppm	ASTM D5185m >4	0	0	0
Titanium	ppm	ASTM D5185m >2	0	1	0
Silver	ppm	ASTM D5185m >2	<1	0	0
Aluminum	ppm	ASTM D5185m >15	2	2	1
Lead	ppm	ASTM D5185m >25	0	0	2
Copper	ppm	ASTM D5185m >100	3	<1	1
Tin	ppm	ASTM D5185m >4	<1	0	0
Vanadium	ppm	ASTM D5185m	0	<1	0
Cadmium	ppm	ASTM D5185m	0	0	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	5	51	<1
Barium	ppm	ASTM D5185m 0	3	0	2
Molybdenum	ppm	ASTM D5185m 60	50	37	52
Manganese	ppm	ASTM D5185m 0	1	0	<1
Magnesium	ppm	ASTM D5185m 1010	768	505	621
Calcium	ppm	ASTM D5185m 1070	911	1472	797
Phosphorus	ppm	ASTM D5185m 1150	829	724	704
Zinc	ppm	ASTM D5185m 1270	982	866	881
Sulfur	ppm	ASTM D5185m 2060	2758	2505	2219

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	12	10	0
Sodium	ppm	ASTM D5185m	34	14	30
Potassium	ppm	ASTM D5185m >20	<1	2	1
Fuel	%	ASTM D3524 >3.0	▲ 15.2	▲ 1.5	▲ 23.9

INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >6	0.4	0.1	0.8
Nitration	Abs/cm	*ASTM D7624 >20	8.7	4.9	9.1
Sulfation	Abs/.1mm	*ASTM D7415 >30	18.8	21.2	18.5


FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	15.4	18.3	14.3
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	7.3	10.5	5.9




OIL ANALYSIS REPORT


Fuel Dilution




FT-IR (Direct Trend)



FT-IR (Direct Trend)



Base Number



VISUAL


	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES


	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4 ▲ 9.9	12.4	▲ 8.1

GRAPHS


Ferrous Alloys




Non-ferrous Metals



Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513

Sample No. : GFL0072139

Lab Number : 06155593

Unique Number : 10991016

Test Package : FLEET (Additional Tests: FuelDilution, PercentFuel)

Received : 22 Apr 2024

Tested : 25 Apr 2024

Diagnosed : 25 Apr 2024 - Wes Davis

GFL Environmental - 094 - Cedartown

2097 Buchanan Highway

Cedartown, GA

US 30125

Contact: WILLIAM FOSTER

william.foster@gflenv.com

T: (800)207-6618

F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)