

# **OIL ANALYSIS REPORT**

Sample Rating Trend



Machine Id
V3642
Component
Diesel Engine

## PETRO CANADA DURON SHP 10W30 (--- GAL)

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

#### Wear

All component wear rates are normal.

### Contamination

Elevated aluminum (Al) and/or lead (Pb) and potassium (K) levels in your metals analysis are likely a result of solder flux release into the lubricant and is common on new equipment/components. There is no indication of any contamination in the oil.

## **Fluid Condition**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

GAL)			Jun2023	Apr <b>2</b> 024		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0112744	PCA0099402	
Sample Date		Client Info		03 Apr 2024	06 Jun 2023	
Machine Age	mls	Client Info		189962	158608	
Oil Age	mls	Client Info		0	0	
Oil Changed		Client Info		Changed	Changed	
Sample Status				NORMAL	ABNORMAL	
CONTAMINAT	ION	method	limit/base	current	history1	history2
Fuel		WC Method	>5	<1.0	<1.0	
Water		WC Method	>0.2	NEG	NEG	
Glycol		WC Method		NEG	NEG	
WEAR METAL	S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	65	53	
Chromium	ppm	ASTM D5185m	>20	3	2	
Nickel	ppm	ASTM D5185m	>4	0	0	
Titanium	ppm	ASTM D5185m		<1	<1	
Silver	ppm	ASTM D5185m	>3	0	0	
Aluminum	ppm	ASTM D5185m	>20	17	12	
Lead	ppm	ASTM D5185m	>40	0	0	
Copper	ppm	ASTM D5185m	>330	6	2	
Tin	ppm	ASTM D5185m	>15	<1	0	
Vanadium	ppm	ASTM D5185m		0	<1	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	2	3	25	
Barium	ppm	ASTM D5185m	0	1	0	
Molybdenum	ppm	ASTM D5185m	50	59	78	
Manganese	ppm	ASTM D5185m	0	2	<1	
Magnesium	ppm	ASTM D5185m	950	871	749	
Calcium	ppm	ASTM D5185m	1050	1268	1280	
Phosphorus	ppm	ASTM D5185m	995	1022	764	
Zinc	ppm	ASTM D5185m	1180	1222	897	
Sulfur	ppm	ASTM D5185m	2600	3687	2795	
CONTAMINAN	TS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	12	9	
Sodium	ppm	ASTM D5185m		5	5	
Potassium	ppm	ASTM D5185m	>20	44	23	
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	2.8	<b>▲</b> 3.2	
Nitration	Abs/cm	*ASTM D7624	>20	12.2	11.9	
Sulfation	Abs/.1mm	*ASTM D7415	>30	25.8	24.8	
FLUID DEGRAD	DATION	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	17.9	16.7	
Base Number (BN)	mg KOH/g	ASTM D2896		6.1	6.7	



# **OIL ANALYSIS REPORT**







Certificate 12367

Laboratory Sample No.

: WearCheck USA - 501 Madison Ave., Cary, NC 27513

: PCA0112744 Lab Number : 06155735 Unique Number : 10991158

Received **Tested** 

: 23 Apr 2024 Diagnosed : 23 Apr 2024 - Wes Davis Test Package : MOB 1 ( Additional Tests: TBN )

: 22 Apr 2024

To discuss this sample report, contact Customer Service at 1-800-237-1369.

 $^st$  - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

**MILLER TRUCK LEASING #137** 

361 ROUTE 312 BREWSTER, NY

US 10509 Contact: Robert Beckhusen rbeckhusen@millertransgroup.com

T: (845)779-1064

Report Id: MILBRENY [WUSCAR] 06155735 (Generated: 04/23/2024 17:05:37) Rev: 1

Contact/Location: Robert Beckhusen - MILBRENY