




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Area  
**(14KM6A)**  
 Machine Id  
**928079-260344**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>GFL0114065</b>	GFL0099974	GFL0062956
Sample Date	Client Info	<b>18 Apr 2024</b>	10 Nov 2023	20 Feb 2023
Machine Age	hrs	<b>15563</b>	15442	14374
Oil Age	hrs	<b>0</b>	600	0
Oil Changed	Client Info	<b>Not Chngd</b>	Changed	Changed
Sample Status		<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method >0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method	<b>NEG</b>	NEG	NEG

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >75	<b>11</b>	29	14
Chromium	ppm ASTM D5185m >5	<b>&lt;1</b>	<1	0
Nickel	ppm ASTM D5185m >4	<b>0</b>	<1	0
Titanium	ppm ASTM D5185m >2	<b>&lt;1</b>	<1	0
Silver	ppm ASTM D5185m >2	<b>0</b>	<1	0
Aluminum	ppm ASTM D5185m >15	<b>3</b>	6	3
Lead	ppm ASTM D5185m >25	<b>0</b>	<1	0
Copper	ppm ASTM D5185m >100	<b>14</b>	1	0
Tin	ppm ASTM D5185m >4	<b>&lt;1</b>	0	0
Vanadium	ppm ASTM D5185m	<b>0</b>	0	0
Cadmium	ppm ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	<b>9</b>	10	2
Barium	ppm ASTM D5185m 0	<b>2</b>	8	0
Molybdenum	ppm ASTM D5185m 60	<b>58</b>	54	63
Manganese	ppm ASTM D5185m 0	<b>1</b>	<1	0
Magnesium	ppm ASTM D5185m 1010	<b>904</b>	805	995
Calcium	ppm ASTM D5185m 1070	<b>1162</b>	1072	1124
Phosphorus	ppm ASTM D5185m 1150	<b>1072</b>	978	1055
Zinc	ppm ASTM D5185m 1270	<b>1232</b>	1115	1343
Sulfur	ppm ASTM D5185m 2060	<b>3633</b>	3377	3577

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	<b>8</b>	7	6
Sodium	ppm ASTM D5185m	<b>5</b>	0	3
Potassium	ppm ASTM D5185m >20	<b>&lt;1</b>	2	2

## INFRA-RED

method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >6	<b>0.1</b>	0.5	0.4
Nitration	Abs/cm *ASTM D7624 >20	<b>5.1</b>	8.1	7.8
Sulfation	Abs/.1mm *ASTM D7415 >30	<b>17.5</b>	19.7	19.0


## FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	<b>13.3</b>	15.4	14.8
Base Number (BN)	mg KOH/g ASTM D2896 9.8	<b>9.5</b>	8.2	8.6




# OIL ANALYSIS REPORT


FT-IR (Direct Trend)



Base Number



Viscosity @ 100°C




VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG


FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	13.9	13.4

## GRAPHS


Ferrous Alloys




Non-ferrous Metals



Viscosity @ 100°C



Base Number



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0114065  
**Lab Number** : 06155756  
**Unique Number** : 10991179  
**Test Package** : FLEET

**GFL Environmental - 836 - Kansas City Hauling**  
 7801 East Truman Road  
 Kansas City, MO  
 US 64126  
 Contact: Loyce Stewart  
 loyce.stewart@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: