


# OIL ANALYSIS REPORT

## Sample Rating Trend



**NORMAL**



Area  
**FLEET**  
 Machine Id  
**26376 (S/N 4V4NC9EH4GN963632)**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 10W30 (42 QTS)**

### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.

#### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			<b>PCA0119912</b>	PCA0113712	PCA0105971
Sample Date	Client Info			<b>11 Apr 2024</b>	04 Jan 2024	12 Oct 2023
Machine Age	mls	Client Info		<b>488791</b>	476419	449479
Oil Age	mls	Client Info		<b>39312</b>	26940	30000
Oil Changed	Client Info			<b>Changed</b>	Not Changd	Changed
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>5		<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method	>0.2		<b>NEG</b>	NEG	NEG
Glycol	WC Method			<b>NEG</b>	NEG	NEG

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	<b>32</b>	19	34
Chromium	ppm	ASTM D5185m	>20	<b>1</b>	<1	<1
Nickel	ppm	ASTM D5185m	>4	<b>2</b>	0	<1
Titanium	ppm	ASTM D5185m		<b>&lt;1</b>	0	0
Silver	ppm	ASTM D5185m	>3	<b>&lt;1</b>	0	0
Aluminum	ppm	ASTM D5185m	>20	<b>4</b>	2	3
Lead	ppm	ASTM D5185m	>40	<b>4</b>	1	4
Copper	ppm	ASTM D5185m	>330	<b>65</b>	65	26
Tin	ppm	ASTM D5185m	>15	<b>3</b>	<1	3
Vanadium	ppm	ASTM D5185m		<b>&lt;1</b>	0	0
Cadmium	ppm	ASTM D5185m		<b>&lt;1</b>	0	0




ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	2	<b>1</b>	3	67
Barium	ppm	ASTM D5185m	0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m	50	<b>61</b>	62	65
Manganese	ppm	ASTM D5185m	0	<b>1</b>	0	<1
Magnesium	ppm	ASTM D5185m	950	<b>893</b>	921	397
Calcium	ppm	ASTM D5185m	1050	<b>1137</b>	1176	1769
Phosphorus	ppm	ASTM D5185m	995	<b>1028</b>	1031	1067
Zinc	ppm	ASTM D5185m	1180	<b>1242</b>	1254	1248
Sulfur	ppm	ASTM D5185m	2600	<b>2339</b>	2610	3820

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<b>9</b>	8	22
Sodium	ppm	ASTM D5185m		<b>13</b>	6	1
Potassium	ppm	ASTM D5185m	>20	<b>6</b>	4	4

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	<b>0.4</b>	0.2	0.2
Nitration	Abs/cm	*ASTM D7624	>20	<b>10.8</b>	8.3	7.1
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>22.7</b>	20.4	19.2

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>22.3</b>	17.9	15.7
Base Number (BN)	mg KOH/g	ASTM D2896		<b>3.8</b>	6.5	7.5





# OIL ANALYSIS REPORT



PARAMETER	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	12.00	11.4	10.9

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0119912      **Received** : 22 Apr 2024  
**Lab Number** : **06156674**      **Tested** : 23 Apr 2024  
**Unique Number** : 10992097      **Diagnosed** : 23 Apr 2024 - Wes Davis  
**Test Package** : FLEET

**PERDUE FARMS - ACCOMAC**  
 22520 LANKFORD HWY  
 ACCOMAC, VA  
 US 23301  
 Contact: PEGGY KIMES  
 peggy.kimes@perdue.com  
 T: (757)787-5304  
 F: (757)787-5208

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)