

OIL ANALYSIS REPORT

ISO

Machine Id **MH-89** Component Hydraulic System AW HYDRAULIC OIL ISO 46 (--- GAL)

DIAGNOSIS

Recommendation

We recommend you service the filters on this component. Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

Wear

All component wear rates are normal.

Contamination

There is a light amount of silt (particulates < 14 microns in size) present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Sample Number Client Info PCA0123781 Sample Date Client Info 16 Apr 2024 Machine Age hrs Client Info 7607 Oil Age hrs Client Info 0 Oil Age hrs Client Info 0 Oil Changed Client Info Not Changd Sample Status Imathematical Status I	story2 story2
Sample Date Client Info 16 Apr 2024 Machine Age hrs Client Info 7607 Oil Age hrs Client Info 0 Oil Changed Client Info 0 Oil Changed Client Info Not Changd Sample Status Imathematical Client Info Not Changd Sample Status Imathematical Client Info Not Changd CONTAMINATION method limit/base current history1 hii Water WC Method >0.1 NEG WEAR METALS method limit/base current history1 hii Iron ppm ASTM D5185m<>20 8 Chromium ppm ASTM D5185m<>10 2 Nickel ppm <td< th=""><th>story2 story2</th></td<>	story2 story2
Machine Age hrs Client Info 7607 Oil Age hrs Client Info 0 Oil Changed Client Info Not Changd Sample Status Imathematical Client Info Not Changd CONTAMINATION method limit/base current history1 hii Water WC Method >0.1 NEG WEAR METALS method limit/base current history1 hii Iron ppm ASTM D5185m<>20 8 Nickel ppm ASTM D5185m<>10 2 Nickel ppm ASTM D5185m<>10 <1 Silver ppm ASTM D5185m 0 Aluminum porm ASTM D5185m >10 2	story2 story2
Oil Age hrs Client Info 0 Oil Changed Client Info Not Changd Sample Status Client Info Nat Changd CONTAMINATION method limit/base current history1 history1 Water WC Method >0.1 NEG WEAR METALS method limit/base current history1 history1 Iron ppm ASTM D5185m >20 8 Nickel ppm ASTM D5185m >10 2 Nickel ppm ASTM D5185m >10 <1	story2 story2
Oil Changed Client Info Not Changd Sample Status Image: Sample	story2 story2
Sample StatusATTENTIONCONTAMINATIONmethodlimit/basecurrenthistory1hiWaterWC Method>0.1NEGWEAR METALSmethodlimit/basecurrenthistory1hiIronppmASTM D5185m>208ChromiumppmASTM D5185m>102NickelppmASTM D5185m>10<1TitaniumppmASTM D5185m<10<1SilverppmASTM D5185m0AluminumppmASTM D5185m>102	story2 story2
CONTAMINATIONmethodlimit/basecurrenthistory1hiWaterWC Method>0.1NEGWEAR METALSmethodlimit/basecurrenthistory1history1IronppmASTM D5185m>208ChromiumppmASTM D5185m>102NickelppmASTM D5185m>10<1TitaniumppmASTM D5185m<1SilverppmASTM D5185m0AluminumppmASTM D5185m>102	story2 story2
Water WC Method >0.1 NEG WEAR METALS method limit/base current history1 hi Iron ppm ASTM D5185m >20 8 Chromium ppm ASTM D5185m >10 2 Nickel ppm ASTM D5185m >10 <1 Titanium ppm ASTM D5185m 0 <1 Silver ppm ASTM D5185m 0 Aluminum ppm ASTM D5185m >10	story2
Water WC Method >0.1 NEG WEAR METALS method limit/base current history1 hi Iron ppm ASTM D5185m >20 8 Chromium ppm ASTM D5185m >10 2 Nickel ppm ASTM D5185m >10 <1 Titanium ppm ASTM D5185m 0 <1 Silver ppm ASTM D5185m 0 Aluminum ppm ASTM D5185m >10 2	story2
WEAR METALS method limit/base current history1 history1 Iron ppm ASTM D5185m >20 8 Chromium ppm ASTM D5185m >10 2 Nickel ppm ASTM D5185m >10 <1 Titanium ppm ASTM D5185m 0 <1 Silver ppm ASTM D5185m 0 Aluminum ppm ASTM D5185m >10 2	story2
Iron ppm ASTM D5185m >20 8 Chromium ppm ASTM D5185m >10 2 Nickel ppm ASTM D5185m >10 <1	
Chromium ppm ASTM D5185m >10 2 Nickel ppm ASTM D5185m >10 <1 Titanium ppm ASTM D5185m <10 <1 Silver ppm ASTM D5185m 0 Aluminum ppm ASTM D5185m >10 2	
Nickel ppm ASTM D5185m >10 <1	
Titanium ppm ASTM D5185m <1	
Silver ppm ASTM D5185m 0 Aluminum ppm ASTM D5185m >10 2	
Aluminum ppm ASTM D5185m >10 2	
Lead ppm ASTM D5185m >10 <1	
Copper ppm ASTM D5185m >75 2	
Tin ppm ASTM D5185m >10 <1	
Vanadium ppm ASTM D5185m <1	
Cadmium ppm ASTM D5185m <1	
ADDITIVES method limit/base current history1 hi	story2
Boron ppm ASTM D5185m 5 0	
Barium ppm ASTM D5185m 5 0	
Molybdenum ppm ASTM D5185m 5 <1	
Manganese ppm ASTM D5185m 0	
Magnesium ppm ASTM D5185m 25 2	
Calcium ppm ASTM D5185m 200 190	
Phosphorus ppm ASTM D5185m 300 358	
Zinc ppm ASTM D5185m 370 489	
Sulfur ppm ASTM D5185m 2500 1157	
CONTAMINANTS method limit/base current history1 hi	story2
Silicon ppm ASTM D5185m >20 1	
Sodium ppm ASTM D5185m 0	
Potassium ppm ASTM D5185m >20 1	
Potassium ppm ASTM D5185m >20 1 FLUID CLEANLINESS method limit/base current history1 history1	story2
Potassium ppm ASTM D5185m >20 1 FLUID CLEANLINESS method limit/base current history1 history1 Particles >4μm ASTM D7647 >5000 5032	story2
Potassium ppm ASTM D5185m >20 1 FLUID CLEANLINESS method limit/base current history1 history2	story2
Potassium ppm ASTM D5185m >20 1 FLUID CLEANLINESS method limit/base current history1 history2 history2 history2 history2 history2 history2	story2
Potassium ppm ASTM D5185m >20 1 FLUID CLEANLINESS method limit/base current history1 history1 Particles >4µm ASTM D7647 >5000 5032 Particles >6µm ASTM D7647 >1300 1132 Particles >14µm ASTM D7647 >160 83 Particles >21µm ASTM D7647 >40 20	story2
Potassium ppm ASTM D5185m >20 1 FLUID CLEANLINESS method limit/base current history1 history1 Particles >4µm ASTM D7647 >5000 5032 Particles >6µm ASTM D7647 >1300 1132 Particles >14µm ASTM D7647 >160 83 Particles >21µm ASTM D7647 >40 20 Particles >38µm ASTM D7647 >10 1	story2
Potassium ppm ASTM D5185m >20 1 FLUID CLEANLINESS method limit/base current history1 hi Particles >4µm ASTM D7647 >5000 5032 Particles >6µm ASTM D7647 >1300 1132 Particles >6µm ASTM D7647 >160 83 Particles >14µm ASTM D7647 >160 83 Particles >21µm ASTM D7647 >10 1 Particles >38µm ASTM D7647 >10 1 Particles >71µm ASTM D7647 >3 0	story2
Potassium ppm ASTM D5185m >20 1 FLUID CLEANLINESS method limit/base current history1 hi Particles >4µm ASTM D7647 >5000 5032 Particles >6µm ASTM D7647 >1300 1132 Particles >6µm ASTM D7647 >160 83 Particles >14µm ASTM D7647 >40 20 Particles >21µm ASTM D7647 >10 1 Particles >38µm ASTM D7647 >3 0 Oil Cleanliness ISO 4406 (c) >19/17/14 20/17/14	story2
Potassium ppm ASTM D5185m >20 1 FLUID CLEANLINESS method limit/base current history1 hi Particles >4µm ASTM D7647 >5000 5032 Particles >6µm ASTM D7647 >1300 1132 Particles >6µm ASTM D7647 >160 83 Particles >14µm ASTM D7647 >160 83 Particles >21µm ASTM D7647 >10 1 Particles >38µm ASTM D7647 >10 1 Particles >71µm ASTM D7647 >3 0 Oil Cleanliness ISO 4406 (c) >19/17/14 20/17/14 FLUID DEGRADATION method limit/base current history1 history1	story2 story2

Report Id: SCRMIN [WUSCAR] 06157637 (Generated: 04/24/2024 12:38:53) Rev: 1

Contact/Location: FRANK NALLY - SCRMIN Page 1 of 2



OIL ANALYSIS REPORT









To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: SCRMIN [WUSCAR] 06157637 (Generated: 04/24/2024 12:38:53) Rev: 1

Certificate 12367

Laboratory

Sample No.

Contact/Location: FRANK NALLY - SCRMIN

T:

F: