


OIL ANALYSIS REPORT

Sample Rating Trend









Machine Id
DT644
Component
Transmission (Auto)
Fluid

Fluid COGNIS EMGARD 2805 ATF (15 mls)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the fluid.

Fluid Condition


The condition of the fluid is acceptable for the time in service.

05 ATF (15 mls)		Jul2019	Dec2020 Oct2021	Aug2022 May2023	Apr2024	
SAMPLE INFOR	RMATION	method	limit/base	current	history1	history2
	IIVIATION		mmbasc			
Sample Number		Client Info		PCA0111581	PCA0101825	PCA0095250
Sample Date		Client Info		02 Apr 2024	25 Oct 2023	24 May 2023
Machine Age	mls	Client Info		73114	73114	73114
Oil Age	mls	Client Info		73114	73114	73114
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL
CONTAMINA	ΓΙΟΝ	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG	NEG	NEG
WEAR METAI	LS	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>220	32	57	56
Chromium	ppm	ASTM D5185m	>2	0	0	<1
Nickel	ppm	ASTM D5185m	>5	0	<1	<1
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m	>5	0	0	0
Aluminum	ppm	ASTM D5185m	>75	13	23	25
Lead	ppm	ASTM D5185m	>95	6	10	10
Copper	ppm	ASTM D5185m	>60	14	21	21
Tin	ppm	ASTM D5185m	>10	0	2	2
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		117	154	167
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		3	0	2
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m		11	12	7
Calcium	ppm	ASTM D5185m		183	125	137
Phosphorus	ppm	ASTM D5185m		324	366	406
Zinc	ppm	ASTM D5185m		66	68	74
Sulfur	ppm	ASTM D5185m		2150	1664	2011
CONTAMINA	NTS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	5	8	8
Sodium	ppm	ASTM D5185m		4	5	3
Potassium	ppm	ASTM D5185m	>20	0	2	2
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	LIGHT
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
3:36:03) Rev: 1						· DAVID WERR

Submitted By: DAVID WEBB





OIL ANALYSIS REPORT




FLUID PROP	ERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	38.9	34.3	36.0	36.1
SAMPLE IMA	GES	method	limit/base	current	history1	history2
Color				no image	no image	no image
Bottom				no image	no image	no image

GRAPHS









Certificate 12367

Laboratory

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Sample No. : PCA0111581 Lab Number : 06158183 Unique Number : 10993606

Received : 23 Apr 2024 **Tested** Diagnosed

: 24 Apr 2024 : 24 Apr 2024 - Wes Davis

NW WHITE & CO - BEAUFORT DIVISION 1491 YENMASSEE HIGHWAY VARNVILLE, SC

US 29944 Contact: VINCENT BULLOCK

bullockvince514@gmail.com T:

Test Package : FLEET To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: