


# **OIL ANALYSIS REPORT**

Sample Rating Trend







Machine Id DT659

Component Transmission (Auto)

**COGNIS EMGARD 2805 ATF (15 mls)** 

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the fluid.

### **Fluid Condition**


The condition of the fluid is acceptable for the time in service.

		Nov2019 Dec2	020 Jul2021 Jan2022 Aug20	022 Dec2022 May2023 Aug2023 Dec2	023 Apr2024		
SAMPLE INFORM	/ATION	method	limit/base	current	history1	history2	
Sample Number		Client Info		PCA0111570	PCA0111651	PCA0101878	
Sample Date		Client Info		12 Apr 2024	15 Dec 2023	28 Aug 2023	
Machine Age	mls	Client Info		28393	28393	28393	
Oil Age	mls	Client Info		28393	28393	28393	
Oil Changed		Client Info		N/A	N/A	N/A	
Sample Status				NORMAL	NORMAL	NORMAL	
CONTAMINATI	ON	method	limit/base	current	history1	history2	
Water		WC Method	>0.1	NEG	NEG	NEG	
WEAR METALS	3	method	limit/base	current	history1	history2	
Iron	ppm	ASTM D5185m	>160	44	39	68	
Chromium	ppm	ASTM D5185m	>5	0	<1	<1	
Nickel	ppm	ASTM D5185m	>5	0	0	0	
Titanium	ppm	ASTM D5185m		0	0	0	
Silver	ppm	ASTM D5185m	>5	0	0	0	
Aluminum	ppm	ASTM D5185m	>50	22	20	31	
Lead	ppm	ASTM D5185m	>50	26	15	25	
Copper	ppm	ASTM D5185m	>225	41	27	34	
Tin	ppm	ASTM D5185m	>10	<1	2	4	
Vanadium	ppm	ASTM D5185m		0	<1	0	
Cadmium	ppm	ASTM D5185m		0	0	0	
ADDITIVES		method	limit/base	current	history1	history2	
Boron	ppm	ASTM D5185m		111	113	106	
Barium	ppm	ASTM D5185m		0	0	0	
Molybdenum	ppm	ASTM D5185m		2	2	<1	
Manganese	ppm	ASTM D5185m		<1	<1	2	
Magnesium	ppm	ASTM D5185m		7	0	4	
Calcium	ppm	ASTM D5185m		153	116	76	
Phosphorus	ppm	ASTM D5185m		307	247	314	
Zinc	ppm	ASTM D5185m		61	44	52	
Sulfur	ppm	ASTM D5185m		1815	1380	1199	
CONTAMINAN <sup>*</sup>	TS	method	limit/base	current	history1	history2	
Silicon	ppm	ASTM D5185m	>20	5	5	7	
Sodium	ppm	ASTM D5185m		4	3	6	
Potassium	ppm	ASTM D5185m	>20	0	<1	4	
VISUAL		method	limit/base	current	history1	history2	
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE	
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE	
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE	
Silt	scalar	*Visual	NONE	NONE	NONE	NONE	
Debris	scalar	*Visual	NONE	NONE	NONE	NONE	
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE	
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML	
Odor	scalar	*Visual	NORML	NORML	NORML	NORML	
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG	
Free Water	scalar	*Visual		NEG	NEG	NEG	
3:36:10) Rev: 1					Submitted By: DAVID WEBB		

Submitted By: DAVID WEBB





# **OIL ANALYSIS REPORT**




FLUID PROPE	RTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	38.9	34.1	34.8	36.0
SAMPLE IMAG	GES	method	limit/base	current	history1	history2
Color				no image	no image	no image
Bottom				no image	no image	no image

# **GRAPHS**









Certificate 12367

Laboratory

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Sample No. : PCA0111570 Lab Number : 06158186 Unique Number : 10993609

Test Package : FLEET

Received : 23 Apr 2024 **Tested** Diagnosed

: 24 Apr 2024

: 24 Apr 2024 - Wes Davis

**NW WHITE & CO - BEAUFORT DIVISION** 1491 YENMASSEE HIGHWAY

VARNVILLE, SC US 29944

Contact: VINCENT BULLOCK bullockvince514@gmail.com

To discuss this sample report, contact Customer Service at 1-800-237-1369. \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:

F: