


OIL ANALYSIS REPORT



(C0810283) {UNASSIGNED} 834016

Component
Natural Gas Engine

PETRO CANADA DURON SHP 15W40 (8 GAL)





DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.


	` ′					
SAMPLE INFOR	RMATION	method	limit/base	current	history1	history2
Sample Number		Client Info		GFL0118026	GFL0109914	GFL0109870
Sample Date		Client Info		23 Apr 2024	29 Jan 2024	12 Jan 2024
Machine Age	hrs	Client Info		1212	1194	1098
Oil Age	hrs	Client Info		27	594	507
Oil Changed		Client Info		Not Changd	Changed	Not Changd
Sample Status				NORMAL	NORMAL	NORMAL
CONTAMINA	TION	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG	NEG	NEG
WEAR METAI	LS	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	25	23	28
Chromium	ppm	ASTM D5185m	>4	0	<1	<1
Nickel	ppm	ASTM D5185m	>2	0	<1	<1
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>9	0	2	2
Lead	ppm	ASTM D5185m	>30	0	4	3
Copper	ppm	ASTM D5185m	>35	<1	4	5
Tin	ppm	ASTM D5185m	>4	0	2	1
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	12	0	0
Barium	ppm	ASTM D5185m	0	0	0	3
Molybdenum	ppm	ASTM D5185m	60	66	61	66
Manganese	ppm	ASTM D5185m	0	<1	2	2
Magnesium	ppm	ASTM D5185m	1010	991	865	956
Calcium	ppm	ASTM D5185m	1070	1226	1042	1139
Phosphorus	ppm	ASTM D5185m	1150	1121	848	882
Zinc	ppm	ASTM D5185m	1270	1394	1111	1174
Sulfur	ppm	ASTM D5185m	2060	3822	2479	3017
CONTAMINA	NTS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>+100	3	9	9
Sodium	ppm	ASTM D5185m		<1	6	4
Potassium	ppm	ASTM D5185m	>20	<1	3	4
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844		0	0	0
Nitration	Abs/cm	*ASTM D7624	>20	5.5	10.0	9.9
Sulfation	Abs/.1mm	*ASTM D7415	>30	17.9	21.7	20.3
FLUID DEGRA	DATION	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	12.8	16.1	15.4
Daga Number (DNI)		ACTM DOOOC	0.0	77	0.0	0.4


7.7


Base Number (BN) mg KOH/g ASTM D2896 9.8



OIL ANALYSIS REPORT










VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG


FLUID PROP	ERTIES	method				history2
Visc @ 100°C	cSt	ASTM D445	15.4	13.7	13.1	13.2

GRAPHS













Certificate 12367

Laboratory Sample No.

Lab Number : 06158743 Unique Number : 10994166

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : GFL0118026

Tested Test Package : FLEET

: 24 Apr 2024 : 25 Apr 2024

Diagnosed : 25 Apr 2024 - Wes Davis

GFL Environmental - 010 - Stockbridge

1280 Rum Creek Parkway Stockbridge, GA

US 30281

Contact: JOSHUA TINKER joshuatinker@gflenv.com

T:

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

To discuss this sample report, contact Customer Service at 1-800-237-1369.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Received

F: