


OIL ANALYSIS REPORT

Area
K5 CONSTRUCTION CORPORATION - HODGKINS IL
 Machine Id
2028
 Component
3 Conveyor Gearbox
 Fluid
LEAHY WOLF SYNMASTER 75W90 (2 GAL)

Sample Rating Trend



NORMAL



DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		PCA0122067	LW0004320	LWI-K74361
Sample Date	Client Info		19 Apr 2024	11 Feb 2022	23 Apr 2018
Machine Age	hrs	Client Info	5847	5818	5331
Oil Age	hrs	Client Info	29	395	2365
Oil Changed		Client Info	Changed	Changed	Changed
Sample Status			NORMAL	NORMAL	SEVERE

CONTAMINATION

	method	limit/base	current	history1	history2
Water	WC Method	>0.2	NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >200	19	11	▲ 850
Chromium	ppm	ASTM D5185m >10	<1	0	▲ 11
Nickel	ppm	ASTM D5185m >10	2	<1	1
Titanium	ppm	ASTM D5185m	<1	<1	0
Silver	ppm	ASTM D5185m	<1	0	0
Aluminum	ppm	ASTM D5185m	2	0	0
Lead	ppm	ASTM D5185m	1	0	0
Copper	ppm	ASTM D5185m	1	0	11
Tin	ppm	ASTM D5185m	1	<1	0
Antimony	ppm	ASTM D5185m >5	---	0	0
Vanadium	ppm	ASTM D5185m	<1	0	0
Cadmium	ppm	ASTM D5185m	1	0	0


ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 328	291	330	240
Barium	ppm	ASTM D5185m 1	<1	0	2
Molybdenum	ppm	ASTM D5185m	1	<1	5
Manganese	ppm	ASTM D5185m	1	0	10
Magnesium	ppm	ASTM D5185m 1	<1	<1	2
Calcium	ppm	ASTM D5185m 7	9	6	264
Phosphorus	ppm	ASTM D5185m 1145	1290	1291	1168
Zinc	ppm	ASTM D5185m 3	18	0	120
Sulfur	ppm	ASTM D5185m 17909	25204	20514	---
Lithium	ppm	ASTM D5185m	---	---	12

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	5	4	8
Sodium	ppm	ASTM D5185m	0	<1	13
Potassium	ppm	ASTM D5185m >20	2	<1	9

OIL ANALYSIS REPORT












VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	99.6	94.8	98.8

SAMPLE IMAGES	method	limit/base	current	history1	history2
---------------	--------	------------	---------	----------	----------

Color				no image	no image	no image
Bottom				no image	no image	no image

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0122067
Lab Number : 06159936
Unique Number : 10995359
Test Package : MOB 1
Received : 24 Apr 2024
Tested : 25 Apr 2024
Diagnosed : 26 Apr 2024 - Don Baldrige

K5 CONSTRUCTION CORPORATION
 6301 S EAST AVENUE
 HODGKINS, IL
 US 60525
 Contact: FRANCISCO MUNOZ
 francisco@k-five.net

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)